SPHERES



14" Smooth Acrylic

DESCRIPTION

LBS smooth spheres are designed for commercial and residential post top and pendant applications and are available with fitter neck, neckless and custom openings.

MATERIALS


- Acrylic UV resistant with continuous operating temperature up to 80°C. Maximum transmittance of 92% (clear). Acrylic spheres are available in clear, white, bronze or smoke.
- LD Acrylic UV resistant with continuous operating temperature up to 80°C and transmittance of 90% to 94% (application dependent).



LD ACRYLIC FROST SHOWN

FITTER NECK (F)	ITEM NO.	DIA (SPHERE)	ID (NECK)	OD (NECK)	MATERIAL	COLOR
	20014-CL-6F	14"	5.20"	5.91"	Acrylic	Clear
	20014-WH-6F	14"	5.20"	5.91"	Acrylic	White
	20014-BR-6F	14"	5.20"	5.91"	Acrylic	Bronze
	20014-SM-6F	14"	5.20"	5.91"	Acrylic	Smoke
	20014-LD-6F	14"	5.20"	5.91"	LD Acrylic	Frost
		•	•		•	·

NECKLESS (N)



	ITEM NO.	DIA (SPHERE)	ID (NECK)	OD (NECK)	MATERIAL	COLOF
1	20014-CL-5N	14"	5.25"	N/A	Acrylic	Clear
	20014-WH-5N	14"	5.25"	N/A	Acrylic	White
	20014-BR-5N	14"	5.25"	N/A	Acrylic	Bronze
/	20014-SM-5N	14"	5.25"	N/A	Acrylic	Smoke
/	20014-LD-5N	14"	5.25"	N/A	LD Acrylic	Frost

CUSTOM (XX)		ITEM NO.	DIA (SPHERE)	MIN (OPENING)	MAX (OPENING)	MATERIAL	COLOR
I.D. CUSTOM OPENING See ACCESSORIES section for all optional attachments		20014-CL-XX	14"	5.25"	9.25"	Acrylic	Clear
		20014-WH-XX	14"	5.25"	9.25"	Acrylic	White
		20014-BR-XX	14"	5.25"	9.25"	Acrylic	Bronze
		20014-SM-XX	14"	5.25"	9.25"	Acrylic	Smoke
		20014-LD-XX	14"	5.25"	9.25"	LD Acrylic	Frost

OPTIONAL ACCESSORIES

Aluminum Neck Fitters



98007-A 98007.5-A



Plastic Neck Fitters



98008-PSPEC-WHT 98008-PSPEC-BLK





96005-BLK 96005-WHT

Internal Heat Shields



96104-A

Dimensions are nominal