

Sunlite 49148 LED Roadway Security Light with Photo Control Fixture, Pole Mount, Selectable 36W/48W/60W Power, 7500 Lmns, Selectable 30K/40K/50K Color, UL Listed, Dimmable, Roadway, Commercial Use

Road

DESCRIPTION:

Sunlite's LED Roadway Security Light with Photo Control Fixture gives the security light you need whenever you need it. These fixtures allow you to choose the color temperature at the time of installation. Select 3000K Warm White, 4000K Cool White, or 5000K Daylight depending on your preference using a switch located within the fixture. A second switch allows you to select between wattage for different lumen outputs. Choose 36 watts, 48 watts, or 60 watts. With its bright LEDs and high lumen output from 4320 - 7500, our lights are great for entrance, courtyard, industrial, security, and many more! Made to last thanks to its aluminum material with a dark brown finish. UL Listed for safety and quality. IP65 rated. Great for commercial applications on 120-277-volt service. Dimensions: 4.16" H x 7.01" W x 10.37" D.



FEATURES:

- **DUSK TO DAWN SENSOR** - These roadway light's dusk-to-dawn photocell sensors provide security that, no matter the weather, you will always have light where and when you need it.
- **SELECTABLE COLOR & POWER** - These fixtures allow you to choose the color temperature at the time of installation. Select 3000K Warm White, 4000K Cool White, or 5000K Daylight depending on your preference using a switch located within the fixture. A second switch allows you to select between wattage for different lumen outputs. Choose 36 watts, 48 watts, or 60 watts.
- **MULTIPLE OUTDOOR USE** - With its bright LEDs and high lumen output from 4320 - 7500, our lights are great for entrance, barns, industrial, security, and many more! Made to last thanks to its aluminum material with a dark brown finish. Designed for pole mounting.
- **DIMMABLE** - The lighting output can be changed when connected to an LED-compatible dimmer switch (0-10v), allowing it to adjust the brightness to suit your need.
- **UL LISTED** - UL Listed for safety and quality. IP65 rated. Great for commercial applications on 120-277-volt service. Dimensions: 4.16" H x 7.01" W x 10.37" D.



SPECIFICATIONS:

General Characteristics

Average Rated Hours	50000
Finish	Dark Bronze
Average Life Span Years	46
Dimmable	Yes
Dimming Type	0-10V Low Voltage
Material	Aluminum
Lens Material	Polycarbonate
Lens Finish	Clear

Electrical Characteristics

Watts	36/48/60
Volts	120-277
LED Chip Manufacturer	2835
Power Factor	0.9
Temperature	-40°F-113°F

Light Characteristics

Lumens Brightness	4500/6000/7500
Color Rendering Index CRI	80
Emitted Color	CCT Selectable
Color Temperature Kelvin	30K/40K/50K
Beam Angle	140°
Flicker	Yes

Fixture Characteristics

Mounting	Pole
Fixture Technology	LED
Use Location	Outdoor

Additional Features

Safety Rating Mark	UL Listed - Wet Location
Safety Rated For Canada	Yes
Safety Rated For USA	Yes
Mercury Free	Yes

Product Dimensions

MOL (in)	4.15
Diameter (in)	7
Item Dimension (in)	(W) 10.37 (H) 7.01 (D) 4.16
Package Dimension (in)	(W) 6.3 (H) 7.5 (D) 14.3
Package Weight (lb)	4.81

Product Data

Case Unit Rate	4
Item UPC	653703491486
Warranty Years	5