

## 6" Cylinder LED Wall Sconce

Down

### DESCRIPTION:

6-Inch LED Outdoor Decorative Up or Downlight, Modern Cylinder Wall Sconce Fixture, 12 Watts, 1000 Lumens, Selectable CCT, ETL Listed, Brushed Nickel, for Porches, Garage & Entryways

### FEATURES:

- **SLEEK PROFILE** - The LED 6 Inch Up or Down Cylinder Wall Sconce offers effortless and modest lighting to outdoor or indoor spaces. Fixture dimensions are 6" tall, 4.35" wide, and 4.3" deep. Cylinder is 2.75" in diameter. Back plate is 4.35" tall, 4.35" wide, and 0.5" deep.
- **MANY APPLICATIONS** - Understated and modern aesthetic, this fixture will add curb appeal to any home. By providing bright illumination, the cylinder luminaire makes for great lighting near your garage entrance. The minimalistic wall sconce spreads proper light over surrounding walls and ground. Its recessed LEDs and diffuser soften the light making it perfect for porches, gateways, and entryways.
- **GEOMETRIC DESIGN** - The energy-efficient LED wall sconce is a modern-day lighting mainstay that's low profile and stylish. The simplistic wall sconce has a geometric design that provides a sufficient amount of soft, diffused lighting. Our light would be ideal for placement in areas like hallways, bedrooms, and living rooms.
- **DURABILITY** - The low-maintenance wall sconce sports a solid aluminum and steel construction, so it is built to last. Its recessed lighting and robust housing allow a greater degree of durability within its application space. Mount it upwards or downwards for the desired look.
- **WET LISTED & EASY INSTALLATION** - ETL Listed for Wet locations and 120V, which is great for many applications outdoors. Perfect for front lawns, gardens, and balconies, and many more! Designed to be installed directly to a standard junction box on any wall. Hardware and mounting instructions included.



## SPECIFICATIONS:

### General Characteristics

<b>Bulb Shape</b>	Integrated LED
<b>Average Rated Hours</b>	50000
<b>Finish</b>	Brushed Nickel
<b>Average Life Span Years</b>	46
<b>Dimmable</b>	Yes
<b>Dimming Type</b>	Forward Phase (Triac or Incandescent)
<b>Dimming Percentage</b>	10-100%
<b>Material</b>	Aluminum & Glass
<b>Lens Material</b>	Glass
<b>Lens Finish</b>	Clear
<b>Bulb Type</b>	Integrated
<b>Application</b>	Outdoor
<b>Replaceable LED Module</b>	Yes

### Electrical Characteristics

<b>Watts</b>	12
<b>Volts</b>	120
<b>Equivalent Wattage</b>	60
<b>LED Chip Manufacturer</b>	2835
<b>Power Factor</b>	0.98
<b>Temperature</b>	-4°F - 113°F

### Light Characteristics

<b>Lumens Brightness</b>	1000
<b>Color Rendering Index CRI</b>	80
<b>Emitted Color</b>	CCT Selectable
<b>Color Temperature Kelvin</b>	30K/40K/50K
<b>Beam Angle</b>	133°

### Fixture Characteristics

<b>Style</b>	Modern
<b>Shape</b>	Cylinder
<b>Number of Lights</b>	1
<b>Mounting</b>	Wall
<b>Fixture Technology</b>	LED
<b>Use Location</b>	Outdoor

### Additional Features

<b>Safety Rating Mark</b>	ETL Listed - Wet Location
<b>Safety Rated For Canada</b>	Yes
<b>Safety Rated For USA</b>	Yes
<b>Mercury Free</b>	Yes

### Product Dimensions

<b>Size</b>	6"
<b>Item Dimension (in)</b>	(W) 4.35 (H) 6 (D) 4.3

### Product Data

<b>Case Unit Rate</b>	6
<b>Item UPC</b>	653703492049