

## Sunlite 85123 LED Mini Wall Pack Outdoor Fixture, Power Selectable 8W/10W/15W/25W, 3500 Lmns, Color Selectable 30K/40K/50K, Dimmable, D2D Photocell, ETL Listed, Bronze, Residential, Commercial

### DESCRIPTION:

Sunlite LED Mini Wall Pack light fixtures are intended to provide ample outdoor lighting. You can choose between 3000K Warm White, 4000K Cool White, and 5000K Daylight at the back of the fixture. Take control of the light emitted with its selectable wattage of 8W/10W/15W/25W. These commercial grade fixtures have a weather-resistant bronze die-cast and a long-lasting clear polycarbonate lens. With a long life-span of 50,000 hours, these fixtures have the highest dust protection level and can tolerate low-pressure water jets from all angles, thanks to their IP 65 classification. It can be dimmed when installed with an LED-compatible 0-10v dimmer. Built-in photocell for automatic dusk to dawn operation. They provide up to a bright 3900-lumen output depending on the wattage. Ideal for security and general-purpose lighting along building perimeters, entryways, and anywhere extra lighting is required. These fixtures are ETL Listed for wet location installation and not rated for enclosed fixtures. They operate on 120–277-volt service. Fixture Dimension 8.2" H x 5.5" W x 3.4" L.

### FEATURES:

- **COLOR & POWER SELECTABLE** - Sunlite LED Mini Wall Pack light fixtures are intended to provide ample outdoor lighting. It has cutting-edge technology that allows you to customize the color temperature and power before installation. You can choose between 3000K Warm White, 4000K Cool White, and 5000K Daylight at the back of the fixture. Take control of the light emitted with its selectable wattage of 8W/10W/15W/25W.
- **MULTIPLE OUTDOOR USES** - These commercial grade fixtures have a weather-resistant bronze die-cast and a long-lasting clear polycarbonate lens. With a long life-span of 50,000 hours, these fixtures have the highest dust protection level and can tolerate low-pressure water jets from all angles, thanks to their IP 65 classification.
- **DIMMABLE** - It can be dimmed when installed with an LED-compatible 0-10v dimmer.

▪ **BUILT-IN PHOTOCELL** - Built-in photocell for automatic dusk to dawn operation. They provide up to a bright 3900-lumen output depending on the wattage. Ideal for security and general-purpose lighting along building perimeters, entryways, and anywhere extra lighting is required. These fixtures are ETL Listed for wet location installation and not rated for enclosed fixtures. They operate on 120–277-volt service. Fixture Dimension 8.2" H x 5.5" W x 3.4" L.



8.2" H x 5.5" W x 3.4" L.

## SPECIFICATIONS:

### General Characteristics

|                         |                          |
|-------------------------|--------------------------|
| Average Rated Hours     | 50000                    |
| Finish                  | Bronze                   |
| Average Life Span Years | 46                       |
| Dimmable                | Yes                      |
| Dimming Type            | 0-10V Low Voltage        |
| Dimming Percentage      | 0-100%                   |
| Material                | Aluminum & Polycarbonate |
| Lens Material           | Polycarbonate            |
| Lens Finish             | Frosted                  |
| Application             | Outdoor                  |

### Product Dimensions

|                        |                          |
|------------------------|--------------------------|
| Item Dimension (in)    | (W) 5.5 (H) 8.2 (D) 3.4  |
| Package Dimension (in) | (W) 3.8 (H) 6.75 (D) 8.5 |
| Package Weight (lb)    | 2.67                     |

### Product Data

|                |              |
|----------------|--------------|
| Case Unit Rate | 10           |
| Pack Size      | 1            |
| Item UPC       | 653703851235 |
| Warranty Years | 5            |

### Electrical Characteristics

|                       |               |
|-----------------------|---------------|
| Watts                 | 8/10/15/25    |
| Volts                 | 120-277       |
| LED Chip Manufacturer | 3030          |
| Power Factor          | 0.92          |
| Temperature           | -40°F - 104°F |

### Light Characteristics

|                           |                     |
|---------------------------|---------------------|
| Lumens Brightness         | 1160/1450/2175/3625 |
| Color Rendering Index CRI | 70                  |
| Emitted Color             | CCT Selectable      |
| Color Temperature Kelvin  | 30K/40K/50K         |
| Beam Angle                | 120°                |

### Fixture Characteristics

|                    |         |
|--------------------|---------|
| Mounting           | Wall    |
| Fixture Technology | LED     |
| Use Location       | Outdoor |

### Additional Features

|                         |                           |
|-------------------------|---------------------------|
| Safety Rating Mark      | ETL Listed - Wet Location |
| Safety Rated For Canada | Yes                       |
| Safety Rated For USA    | Yes                       |
| DLC                     | Yes                       |
| DLC Number              | S-O5P2EL                  |
| DLC Classification      | Premium                   |
| Mercury Free            | Yes                       |