

Sunlite 88918-SU LED Dual Head Outdoor Security Light with Motion Sensor and Photocell, White, Warm White, 1800 Lumen

DESCRIPTION:

Sunlite's LED dual head security light delivers super bright light with high energy savings. It features motion detection technology, daylight detection ability and easily rotatable lights and sensor for preferred position. It is ideal for entrance ways, porch lights, garages and general security and safety applications. It draws only 20 watts (replacing 2 PAR38 light bulbs) while producing a super bright 1800 lumen light. Its durable weatherproof aluminum and plastic materials will withstand even extreme weather. The various function options provide full control and flexibility for activating the light. Ontime mode allows the light to run constantly. Auto mode allows it to activate only when motion is detected, with the ability to control the detection distance with a range of 19.5 to 69 feet. Time function allows for control of the length of time the light remains on with a range of 5 seconds to 5 minutes. D2D mode activates the light from dusk to dawn with the ability to control the fixtures sensitivity to daylight. This fixture features a super long life span of 50,000 hours, and is ETL listed for outdoor locations. All mounting hardware is included for simple mounting onto a junction box.

FEATURES:

- Sunlite's LED dual head security light delivers super bright light with high energy savings. It is ideal for entrance ways, porch lights, garages and general security and safety applications
- It draws only 20 watts (replacing 2 PAR38 light bulbs) while producing a super bright 1800 lumen 3000K Warm White light with a 50,000 hour average rated life
- Its durable, weatherproof, aluminum and plastic housing will withstand even extreme weather
- It features motion detection technology with a range control of 19-69 feet and light up time control with a range of 5 seconds-5 minutes. It has a dusk to dawn feature with daylight sensitivity control and easily rotatable lights and sensor
- All mounting hardware is included for simple wall mounting onto a junction box



sunlite

SPECIFICATIONS:

General Characteristics

	Catalog # 88918-SU	
LFX/OPF/MS/20W/30K/WH		

Bulb Shape	Integrated LED	Item Dimension (in)	(W) 5 (H) 6.5 (D) 11.2
Average Rated Hours	50000	ltem Weight (lb)	2.45
Finish	White	Package Dimension (in)	(W) 7.4 (H) 8.3 (D) 8.9
Average Life Span Years	46	Package Weight (lb)	2.45
Dimmable	No		
Material	Aluminum & Plastic	Product Data	
Lens Finish	Clear	Case Unit Rate	6
Bulb Type	Integrated	Item UPC	653703889184

Electrical Characteristics

Watts	20
Volts	120
Equivalent Wattage	150
LED Chip Manufacturer	Sanan
Power Factor	0.9
Temperature	-20° to 55°

Light Characteristics

Lumens Brightness	1800
Color Rendering Index CRI	80
Emitted Color	Warm White
Color Temperature Kelvin	3000K
Beam Angle	100°

Fixture Characteristics

Number of Lights	2
Mounting	Wall
Motion Sensor	Yes
Fixture Technology	LED
Use Location	Outdoor

Additional Features

Safety Rating Mark	ETL Listed - Wet Location
Safety Rated For Canada	Yes
Safety Rated For USA	Yes

Product Dimensions

Warranty Years

5

