

Selectable LED Slim Canopy Light

Wattages: 26W,39W,52W,65W ; 45W,65W,90W,110W



WATT/CCT
SELECTABLE

The Selectable LED Slim Canopy Light can be widely used for Indoor or Outdoor Excellent for Gas station, Hallways, Multipurpose Rooms , Underground parking,super market, store and many other applications.

Lighting controls meet design lights consortium (DLC) networked lighting control system technical requirements, LLLC, Energy Monitoring and High End Trim function.



Features:


- Lumileds LED, high luminous efficiency and long working life.
- High efficiency LED Driver, the wide range input voltage AC120-277V.
- Die Cast aluminium cooling design,high quality and better cooling for LED $T_j < 85^{\circ}\text{C}$.
- Excellent Optics design, greatly improve the light utilization and evenness.
- The 1-10V Dimming type is continuous.
- Motion sensor Control Available (SOLD SEPARATELY).

SPECIFICATION								
TYPE	VCP26395265W27-45K-D				VCP456590110W27-345K-D			
WATTAGE	26W	39W	52W	65W	45W	65W	90W	110W
LUMEN	3929 lm	5575 lm	7132 lm	8525 lm	7342 lm	11188 lm	14741 lm	17325 lm
EFFICACY	> 140 lm/W							
CCT	4000K,5000K				3000K,4000K,5000K			
CRI	> 70							
INPUT VOLTAGE	AC120-277V							
LIGHTING ANGLE	155°							
FACTORY SETTINGS	65W / 110W & 4000K							
LED TYPE	2835							
PF	> 0.95							
DRIVER EFFICIENCY	> 89%							
PROTECTION LEVEL	Wet location							
OPERATING TEMPERATURE	-40°F ~ 104°F							
LIFE TIME	> 50000 hours							
WARRANTY	5 year limited							

Selectable LED Slim Canopy Light

Wattages: 26W,39W,52W,65W ; 45W,65W,90W,110W

DIMENSION:



Specifications:

Shell materials: Aluminum & PC.

Net weight : 2.31Kg (5.1 lbs)

3.54Kg (7.8 lbs)

Finish: Dark Bronze(Standard)



Product Size:241.8mmX241.8mmX77mm

9.52"X9.52"X3.03"

292.5mmX292.5mmX96.5mm

11.52"X11.52"X3.80"


Control Module:



CCT AND WATTAGE SELECTABLE

This fixture has the function of adjusting the lumens output and color temperature on-site.

WATTAGE SELECT



Each model supports 4 positions wattage regulation: 100%, 80%, 60%, 40%

CCT SELECT



Offer three CCT adjustable (3000K, 4000K, 5000K).

CONTROLS (SOLD SEPARATELY)



NLC-MW-SQ-005
Microwave Motion Sensor
(Sensing range: Approximately 12 Feet)



NLC-MW-SQ-006
Microwave Motion Sensor
(Sensing range: Approximately 40 Feet)



RC-100
Microwave Sensor Remote Controller

CP	456590110W	27	345K	Z	Y	E
PRODUCT	POWER	VOLTAGE	CCT	FINISH	CONTROL	CONTROL
CP Led Slim Canopy	26395265 26W/39W 52W/65W 456590110W 45W/65W 90W/110W	27 AC120-277V	45K 4000K/5000K 345K 3000K/4000K/5000K	D (Dark Bronze) W (White) B (Black) S (Silvery)	P - (Photocell)	M Motion Sensor


Selectable LED Slim Canopy Light

Wattages: 26W,39W,52W,65W ; 45W,65W,90W,110W

PHOTOMETRICS:

For complete IES files, please visit our website.

-CP26395265W27-45K-D (65W&4000K)



WSD-CP456590110W27-345K-D (110W&4000K)

