



Minuteman 5™

LED Retrofit Kit + Housing For Full Cut-Off Wall Pack

Contains LED Retrofit Kit and LED Lighting Housing




Made In USA

AC Electronics LED Retrofit Kit + Housing vs. Standard HID Lights

Wall Pack Light Source	Input Wattage	Lifespan Hrs/Yrs	Energy Use (24hrs/day) Annual	Annual Cost (maintenance + electricity) @ \$0.11/kWh	Electrical Cost Savings
HID	165	24,000/ 2.7	1446 kWh	\$159.00	
LED	37	50,000/ 5.7	324 kWh	\$35.65	78%

LED Retrofit Kit
CFCW35/1.0/50



LED Lighting Housing



Minuteman 5™ LED Retrofit Kit + Housing




Model Number AC311/35/1.0

— Includes Housing —

Includes:

- Single-Output Channel, Class 2 LED Driver, Model Number: AC-35C1.0AUA
- 1 PCB LED Array with Samsung LH351B LED mounted to industrial grade aluminum LED Driver bracket (10 LEDs per array)

Wiring Diagram



Warranty

LED Retrofit Kit + Housing warranty is only valid when it is used in a fixture it was designed for unless otherwise approved in writing by AC Electronics. Any other use in any fixture assembly or use with non-AC specified or supplied components will void this warranty.

*AC warrants to the purchaser that this LED Retrofit Kit + Housing will be free from defects in material or workmanship for a period of 5 years from date of manufacture, when operated at a maximum ambient temperature of 110°F or 45°C, when properly installed and under normal conditions of use.

The warranty excludes damage resulting from improper installation or damage caused by fire or severe weather conditions including, but not limited to, lightning and storms. Evidence of direct exposure to water on the failed units voids the warranty.

See www.aceleds.com for complete warranty policy.

Specifications

Item	Specification
Input Voltage	120-277V, 50/60 Hz
Fixture CRI	73
LED Color Temperature	5290K
Fixture Lumens	2986
Fixture Efficacy	80 lumen/Watt
Lumen Maintenance	≥79% @ 5 years
Zonal Lumen Performance	0-90° = 100%; 80-90° = 0.1%
Warranty	5 years*
LED Quantity (Brand: Samsung LH351B)	10
LED TMP Temperature @ 25°C	81.5°C
Input Power	37.3W
Driver Efficiency	84%
Power Factor @ 277V	>0.9
THD @ 277V	<20%
Driver TMP @ 25°C ambient	57.2°C
Noise	<24dB
EMI	FCC part 15
Max Operating Temperature	45°C Ambient
Min Operation Temperature	-40°C Ambient
LED Retrofit Kit Dimensions / Weight	9.62"H x 11.55"W x 7.47"D / 3 lbs.
Assembled Fixture Dimensions / Weight	11.4"H x 12.1"W x 9.25"D / 10 lbs.

Note: LM79 and ies files are available upon request.

Tork® 2107 Photocell

Approved For Use With AC LED Retrofit Kits

- 120/277V 1800 VA Ballast Load
- 1 To 5 FC Turn On Light Level
- 3 To 15 FC Turn Off Light Level
- SPST Switch
- 16 AWG 6 Inch Wire Lead Terminal
- Temperature Rating -40 to 140°F
- 1/2" Conduit Mounting
- Not included, available from secondary sources

