




Questions?

For customer service please call us at 1-310-787-1100
Office Hours: 8:00 a.m. – 5:00 p.m. PST Monday-Friday
www.eurilighting.com



**LED FLAME
HANGING
LIGHT**

PLEASE REVIEW THE INSTRUCTIONS AND WARNINGS LISTED BELOW PRIOR TO PROPER INSTALLATION

WARNINGS	CAUTIONS
<ul style="list-style-type: none"> • Risk of fire / electrical shock. • LED Fixture installation requires knowledge of luminaire electrical systems. • Risk of electric shock – disconnect power at source before installation. • Do not make or alter any open holes in an enclosure of wiring or electrical components during installation. • If lamp or luminaire exhibits abnormal operation (buzzing, flickering, minimal light, etc.), turn off power, remove fixture, and contact us. <p>For more information please visit www.eurilighting.com or call our toll-free number 1-310-787-1100.</p>	<ul style="list-style-type: none"> • Do not use with dimmers. • Do not look directly at the operating LED Fixture. • Do not touch this product with wet hands. • Do not disassemble, repair, or alter lamp. • Designed for outdoor applications only. • Suitable for wet locations. • The luminaires shall be grounded. • Be careful not to touch the lamp pins to the metal housing when installing. • This Device is not intended for use with emergency exits or emergency lights.

INSTALLATION INSTRUCTIONS

<p>1</p>	<p>2</p>	<p>3</p>	<p>4</p>
1. Take out the cross bar.	2. Install cross bar to the outlet box.	3. Remove the two screws on top of the fixture and slide out the E12 socket housing.	4. Install flame bulbs.
<p>5</p>	<p>6</p>		<p>7</p>
5. Tighten two screws.	<p>6. CONNECT FIXTURE Lift fixture to outlet box. Using wire nuts provided connect bare copper wire from fixture to green or bare copper ground(house) wire. If outlet box is ground wire directly to toulet box. Connect white fixture wire(s) to neutral supply wire. Connect black fixture wire(s) to power supply wire.</p>		<p>7. MOUNT FIXTURE Insert fixture mounting screws though holes on the back plate and secure to cross bar by tightening decorative nuts. NOTE: Hand tighten decorative nuts. Do not use any tools as over tightening may occur causing damage to back plate.</p>