

Exit & Emergency

Evade Emergency Wallpack

- Architectural, Die-Cast Aluminum Housing
- Normally-On and Emergency Operation
- Photocell with Enable/Disable Function
- Vandal Resistant Polycarbonate Lens
- Self-Test/Self-Diagnostics
- LED Lifecycle Exceeding 10 Years

Specifications

Description

The Evade Outdoor Emergency Wallpack Series offers a quality emergency lighting solution in a low profile architectural design. This dual function (normally-on and emergency) wallpack is ideal for egress and safety lighting on building exteriors and over doorways.

Electrical

- 120-277 Vac, 60hz input
- Self-testing/self-diagnostics
- Emergency test button and battery charging indicator
- Photocell enable/disable
- Long-life maintenance free NiCad battery
- 24 Hour recharge time
- 5000K CCT redundant leds
- 0°C - 50°C operating temperature

Certifications

- UL924 Wet Location listed
- NFPA 101 and NFPA 70
- CEC T20 compliant



Construction & Mounting

- Contemporary style, die-cast aluminum housing
- Corrosion resistant powder coat finish
- UV-stabilized, prismatic, polycarbonate lens
- Universal J-box mounting pattern on back plate
- Fully sealed and gasketed construction
- 1/2" threaded conduit entry at top of fixture

Exit & Emergency

Evade Emergency Wallpack

Ordering Information

Product SKU	Product Code	Product Description
95014	EV-WPK-EM	Evade Emergency Wallpack

Specifications Table

	EV-WPK-EM
Input Current	.125A(120VAC) - .54A(277VAC)
Input Wattage	15W
Battery	Ni-cad 4.8V 1.8Ah
Lumen Output	1200 LM
CCT	5000K
Recharge Time	24 Hours
Input Voltage	120-277 VAC
Frequency	60Hz
Housing	Die-Cast Aluminum Housing
Testing Function	Self Test/Self-Diagnostics
Operating Temperature	0°C to 50°C
Listings & Compliance	UL 924, CEC Title 20, NFPA 70 & NFPA 101
Environment	Wet Location Listed
Warranty*	2 Year

*All life safety equipment, including emergency lighting for path of egress must be maintained, serviced, and tested in accordance with all National Fire Protection Association (NFPA) and local codes. Failure to perform the required maintenance, service, or testing could jeopardize the safety of occupants and will void all warranties.

Dimensions

