Page 1 of 2



# KT-EMRG-650-CFL2 EMERGENCY BALLAST



iCD

PRODUCT FEATURES	LIGHT OUTPUT: 650 Lumen	BATTERY: 3.6V Sealed Ni
<b>INPUT VOLTS:</b> 120/277V, 60Hz	ILLUMINATION TIME: 90 Minutes	WARRANTY: 5 Years

#### **OPERATING DETAILS**

- For use in new or existing fixtures, with or without an AC ballast, where emergency lighting is needed.
- Operates one lamp in the emergency mode.
- 2-in-1 LED indicator light and push-to-test switch (for mandated code compliance testing).
- Internal battery automatically connects to the fluorescent lamp for minimum 90 minute emergency illumination via an internal solid-state transfer switch.
- A discharged battery completely recharges in 24 hours, via a fully automatic solid-state, two-rate charger.


# LAMP COMPATIBILITY

- Compatible with most one-, two-, three-, and four-lamp electronic, standard and dimming AC ballasts.
- Operates the following lamps under emergency power:

	2-Pin CFL (W)		
No. of Lamps	1		
Wattage	13-26		

# PHYSICAL SPECIFICATIONS

**CASE DIMENSIONS** 



LENGTH	9.50"			
WIDTH	2.40"			
HEIGHT	1.50"			
<b>CASE MATERIAL:</b> Painted Steel (White Finish)				
ADDITIONAL FEATURES:				

2' Flex Conduit on Both Ends of Ballast

## **INITIAL LUMEN OUTPUT**

LAMP	INITIAL LUMENS	
LAIVIP	1-Lamp	
2-Pin PL CF 13W	380	
2-Pin PL CF 18W	550	
2-Pin PL CF 26W	650	

Keystone Technologies • 208 Progress Drive, Montgomeryville, PA 18936 • Phone (800) 464-2680 • Fax (888) 966-0556 • www.keystoneballast.com



# KT-EMRG-650-CFL2 EMERGENCY BALLAST

#### MOUNTING

- UL listed for factory or field installation. Suitable for damp location.
- Can be mounted inside, on top, or remote from the fixture.\*
- Designed to be used in both switched and unswitched fixtures.
- \* When battery packs are remote mounted, the remote distance cannot exceed 1/2 of the distance from ballast to lamp specified by the AC ballast manufacturer. The maximum allowable remote mounting distance is 50 feet.

#### **ORDERING INFORMATION**

ORDER CODE	PACKAGING STYLE	PACK QTY.	ITEM STATUS
KT-EMRG-650-CFL2-DP	Distributor Pack	1	Quick Ship

### **CATALOG NUMBER BREAKDOWN**



Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State codes.

Keystone Technologies • 208 Progress Drive, Montgomeryville, PA 18936 • Phone (800) 464-2680 • Fax (888) 966-0556 • www.keystoneballast.com