


natural^{led}®

Product Engineering Spec

| | |
|--|--|
| | |
| | |

| Product Spec | | | |
|---------------|-------------------------|---------|---|
| Category | Strip Light | PICTURE |  |
| Item Code | 7594 | | |
| Stock Code | LED-FXUSL40/48FR/850/MV | | |
| Mounting | - | | |
| Housing Color | White | | |

| Electric Characteristics | | Photometric Characteristics | |
|--------------------------|------------|-----------------------------|------------|
| Rated Wattage (W) | 40 | Lumen (lm) | 5395 |
| Tested Wattage (W) | 40 | Efficacy (lm/w) | 105 |
| Input Voltage (V) | 120~277 | CRI | >80 |
| Voltage Frequency (Hz) | 50/60 | CCT (K) | 4000 |
| Input Current (A) | 0.34 | Beam Angle (°) | 120 |
| Power Factor | >0.9 | General Characteristics | |
| Replacement Wattage (W) | - | Operating Temperature | -4°F~131°F |
| Surge protect level | <2KV | Storage Temperature | -4°F~131°F |
| Dimmable | Yes, 0-10V | IP rating | IP20 |
| THD | <20% | Rated Life | 50000 hrs |
| | | Warranty | 5 years |

| Product Dimensions | | Suggested Accessory | |
|----------------------|------|---------------------|--|
| Weight (lbs.) | 3.85 | EM driver | |
| Height (in) | 2.9 | Microwave Sensor | |
| Length (in) | 48 | Infrared Sensor | |
| Width (in) | 2.5 | | |
| Mounting Height (ft) | - | | |
| Cable Length (ft) | 23.6 | | |

| Qualifications | | | |
|----------------|-------------------|-------------|---|
| UL/ETL | ETL | LM79 | √ |
| Energy Star | | LM80 | √ |
| DLC | DLC V4.4 Standard | IES File | √ |
| CEC | | FDA | |
| JA8 | | NEMA | |
| FCC | √ | Dimmer List | |
| RoHS | √ | | |

Comments: