


natural^{led}®

Product Engineering Spec

Product Spec			
Category	Area Light	PICTURE	
Order #	7729		
Item #	LED-FXSAL240/50K/DB/3S/480		
Mounting	SB/SF/EA6/Yoke Mount		
Housing Color	Dark Bronze		

Electric Characteristics		Photometric Characteristics	
Rated Wattage (W)	240	Lumen (lm)	30274
Tested Wattage (W)	243.2	Efficacy (lm/w)	124
Input Voltage (V)	347-480	CRI	>70
Voltage Frequency (Hz)	50/60	CCT (K)	5000
Input Current (A)	0.75	Beam Angle (°)	Type 3/Flood
Power Factor	>0.9	General Characteristics	
Replacement Wattage (W)	-	Operating Temperature	-40°F~140°F
Surge protect level	12KV	Storage Temperature	-40°F~140°F
Dimmable	1-10 V	IP rating	IP65
THD	<20%	Rated Life	50000 hrs
		Warranty	5 years

Product Dimensions		Suggested Accessory	
Weight (lbs.)	24.7	Photocell	
Height (in)	3	Motion Sensor	
Length (in)	23.2	Slip Fitter(SF) mount	
Width (in)	15	Swivel Bracket(SB) Mount	
Mounting Height (ft)		Extrusion Arm(EA) Mount	
Cable Length (ft)		Yoke(YK) Mount	

Qualifications			
UL/ETL	ETL	LM79	√
Energy Star		LM80	√
DLC	V4.3 Premium	IES File	√
CEC		FDA	
JA8		NEMA	
FCC	√	Dimmer List	
RoHS	√		

Comments: