


natural^{led}®

Product Engineering Spec

| | |
|--|--|
| | |
| | |

| Product Spec | | | |
|---------------|-------------------------|---------|---|
| Category | Commercial Strip Light | PICTURE |  |
| Item Code | 9266 | | |
| Stock Code | LED-FXCSL42/96FR/850/MV | | |
| Mounting | Surface Mount | | |
| Housing Color | White + Frosted Lens | | |

| Electric Characteristics | | Photometric Characteristics | |
|--------------------------|-------------|-----------------------------|-------------|
| Rated Wattage (W) | 42 | Lumen (lm) | 6797 |
| Tested Wattage (W) | 43.15 | Efficacy (lm/w) | 158 |
| Input Voltage (V) | 120~277 | CRI | 80 |
| Voltage Frequency (Hz) | 50/60 | CCT (K) | 5000 |
| Input Current (A) | 0.3621 | Beam Angle (°) | 110 |
| Power Factor | >0.9 | General Characteristics | |
| Replacement Wattage (W) | 2 x 75W T12 | Operating Temperature | -22°F~122°F |
| Surge protect level | 4KV | Storage Temperature | -40°F~158°F |
| Dimmable | 1-10V | IP rating | IP20 |
| THD | <20% | Rated Life | 50000 hrs |
| | | Warranty | 5 years |
| | | | |

| Product Dimensions | | Suggested Accessory | |
|----------------------|------|---------------------|--|
| Weight (lbs.) | | Microwave Sensor | |
| Height (in) | 3.31 | EM driver | |
| Length (in) | 2*48 | Wireguard | |
| Width (in) | 3.25 | | |
| Mounting Height (ft) | | | |
| Cable Length (ft) | | | |
| | | | |

| Qualifications | | | |
|----------------|--------------|-------------|---|
| UL/ETL | ETL | LM79 | √ |
| Energy Star | | LM80 | √ |
| DLC | V4.4 Premium | IES File | √ |
| CEC | | FDA | |
| JA8 | | NEMA | |
| FCC | √ | Dimmer List | |
| RoHS | √ | | |

Comments: