


# natural<sup>led</sup>®

## Product Engineering Spec


Product Spec			
Category	Slim Wall Pack	PICTURE	
Item Code	9301		
Stock Code	LED-FXSWP15/840/DB		
Mounting	Wall Mount		
Housing Color	Dark Bronze		

Electric Characteristics		Photometric Characteristics	
Rated Wattage (W)	15	Lumen (lm)	2019
Tested Wattage (W)	16.03	Efficacy (lm/w)	126
Input Voltage (V)	120~277	CRI	>80
Voltage Frequency (Hz)	50/60	CCT (K)	4000
Input Current (A)	0.15	Beam Angle (°)	140
Power Factor	>0.9	General Characteristics	
Replacement Wattage (W)	75W	Operating Temperature	-22°F~122°F
Surge protect level	2KV	Storage Temperature	-40°F~158°F
Dimmable	No	IP rating	IP65
THD	<20%	Rated Life	50000 hrs
		Warranty	5 years

Product Dimensions		Suggested Accessory	
Weight (lbs.)		Photocell	
Height (in)	3.9	Slip Fitter Mount	
Length (in)	8	Knuckle Mount	
Width (in)	6.6		
Mounting Height (ft)			
Cable Length (ft)			

Qualifications			
UL/ETL	ETL	LM79	√
Energy Star		LM80	√
DLC	V4.4 Premium	IES File	√
CEC		FDA	
JA8		NEMA	
FCC	√	Dimmer List	
RoHS	√		

**Comments:**  
 Angle Adjustable  
 1/2" knockout (4 ways)  
 Meets ADA regulation