


natural^{led}®

Product Engineering Spec

| | |
|--|--|
| | |
| | |

| Product Spec | | | |
|---------------|--------------------|---------|---|
| Category | LED Wall Pack | PICTURE |  |
| Item Code | 9449 | | |
| Stock Code | FXTWP60/40K/BZ-PHO | | |
| Mounting | Wall Mount | | |
| Housing Color | Bronze | | |

| Electric Characteristics | | Photometric Characteristics | |
|--------------------------|-------------|-----------------------------|---------------|
| Rated Wattage (W) | 60 | Lumen (lm) | 9000 |
| Tested Wattage (W) | 60 | Efficacy (lm/w) | 150 |
| Input Voltage (V) | 120~277 | CRI | 80 |
| Voltage Frequency (Hz) | 50/60 | CCT (K) | 4000 |
| Input Current (A) | 0.5 (@120V) | Beam Angle (°) | Forward Throw |
| Power Factor | >0.9 | General Characteristics | |
| Replacement Wattage (W) | 250~400 | Operating Temperature | -40°F~122°F |
| Surge protect level | 4KV | Storage Temperature | -40°F~140°F |
| Dimmable | 0-10V | IP rating | IP65 |
| THD | ≤20% | Rated Life | 50000 hrs |
| | | Warranty | 5 years |

| Product Dimensions | | Suggested Accessory | |
|----------------------|-------|------------------------------------|--|
| Weight (lbs.) | 6.86 | 120~277V AC EM driver - Item# 7334 | |
| Height (in) | 9.16 | Microwave Sensor - Item# P10234 | |
| Depth | 7.51 | Wireguard - Item# P10004 | |
| Width (in) | 14.29 | | |
| Mounting Height (ft) | | | |
| Cable Length (ft) | | | |

| Qualifications | | | |
|----------------|--------------|-------------|---|
| UL/ETL | ETL/cETL | LM79 | √ |
| Energy Star | | LM80 | √ |
| DLC | V5.1 Premium | IES File | √ |
| CEC | | FDA | |
| JA8 | | NEMA | |
| FCC | √ | Dimmer List | |
| RoHS | √ | | |

Comments:

Photocell Included with Fixture