


# natural<sup>led</sup>®

## Product Engineering Spec


Product Spec			
Category	Commercial Downlight	PICTURE	
Item Code	9468		
Stock Code	LED10CRL30SW-270L9CCT3/MV		
Mounting	Recessed		
Housing Color	White		

Electric Characteristics		Photometric Characteristics	
Rated Wattage (W)	30 / 23 / 18	Lumen (lm)	2700 / 2070 / 1620
Tested Wattage (W)	30	Efficacy (lm/w)	90
Input Voltage (V)	120~277V	CRI	90
Voltage Frequency (Hz)	60	CCT (K)	3000 / 4000 / 5000
Input Current (A)	0.25 (@ 120V)	Beam Angle (°)	110
Power Factor	>0.9	General Characteristics	
Replacement Wattage (W)	120 ~ 150	Operating Temperature	5°F~113°F
Surge protect level	2KV	Storage Temperature	5°F~113°F
Dimmable	0-10V	IP rating	UL Wet Location
THD	<20%	Rated Life	50000 hrs.
		Warranty	5 years

Product Dimensions		Suggested Accessory	
Weight (lbs.)	1.98	Emergency Driver - Item# 7337	
Height (in)	5.05		
Length (in)	11.22		
Width (in)	11.22		
Mounting Height (ft.)			
Cable Length (ft.)			

Qualifications			
UL/ETL	UL / cUL	LM79	√
Energy Star	√	LM80	√
DLC		IES File	√
CEC		IC Rated	√
JA8	√	Air-tight Rated	√
FCC	√	Dimmer List	
RoHS	√		

Comments: