

Version	2.0	Date	1/7/2022
Prepared By	J.C		

PRODUCT SPECIFICATION

Category	HID retrofit kit
Item Number	9601
Stock Code	RKIT100HID/8CCT3
Mounting	Yoke/E39
Housing Color	Black



ELECTRICAL CHARACTERISTICS

Rated Wattage (W)	100	Replacement Wattage (W)	250-400
Tested Wattage (W)	100		
Input Voltage (V)	100 ~ 277	Surge Protect Level	4KV
Voltage Frequency (Hz)	50/60	Dimmable	0-10V
Input Current (A)	0.84 @120V	AUX (12V) Line	YES
Power Factor	>0.9		
THD	≤ 20%		

PHOTOMETRIC CHARACTERISTICS

Lumen (lm)	12,978	CCT (K)	3000/4000/5000
Efficacy (lm/w)	130	Beam Angle (°)	120deg
CRI	>80		

GENERAL CHARACTERISTICS




Operating Temperature (°F)	-40 ~ 140
Storage Temperature (°F)	-40 ~ 140
IP Rating	-
IK Rating	-
Rated Life	50000 hrs.
Warranty	5 Years

ACCESSORIES

Item #	Stock Code	Description
P10389	SPD-L-10KV-277	Surge protector-Long 10KV 120-277V
P10390	SPD-L-20KV-277	Surge protector-Long 20KV 120-277V
P10374	MT-RKIT-E26	E26 adaptor for HID Retrofit kit

PRODUCT DIMENSIONS

Width- in (mm)	2.73"	91mm
Height- in (mm)	1.44"	48mm
Length- in (mm)	4.8"	160mm
EPA (ft²)	-	
Weight (lbs)	-	
Mounting Height (ft)	-	
Cable Length (in)	25"	



A=4.8in (160mm)
 B=2.73in (91mm)
 C=1.44in (48mm)
 D=4.68in (156mm)
 E=5.22in (174mm)

CERTIFICATIONS

UL/ETL	ETL/cETL	CEC	
NSF / ETL Sanitation		JAS	
Energy Star		FCC	✓
DLC	V5.1 Premium	RoHs	✓

DOCUMENTS

LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS

--