

PROJECT:

SCHEDULE:

DATE:

PREPARE BY:

NOTES:

DESCRIPTION

naturaLED® Title 24/JA8-2016 Recessed Downlight (CRI90) Retrofits are a simple LED lighting solution to replace 60W to 120W incandescent recessed lamp types. Designed as an energy efficient lighting solution for the industry's most popular 4 to 6 inch recessed downlight fixtures. Easy installation and certified Air-Tight, our retrofit recessed downlights are dimmable, CRI 90 rated and come with an E26 adapter. The 5 to 6 inch model has torsion clips that are adjustable and will easily fit in a 5 or 6 inch recessed can.

APPLICATIONS

Bathroom, Over Mirror, Accent, Residential, Hospitality



FEATURES

- Energy Star Certified
- For Damp Location
- Title 24
- Certified Air-Tight per ASTM E283-04
- Uniform light distribution and consistent color
- Built-in power connector with adjustable torsion clips
- Color Temp Selectable: 3000K, 4000K, 5000K
- Input line voltage: 120V
- CRI: 90
- Powerfactor >0.9
- Dimmable
- Beam Angle: Flood
- Operating temperature: - 4°F - 104°F
- 5 Year Warranty
- Finish: White
- Optional for Purchase: GU24 Base, Trims

ACCESSORIES

	GU24 Base
	Trim Options
	E26 Base (Included)

SAMPLE NUMBER LED4RL9-54L930

STYLE	DIAMETER	SERIES	WATTAGE	LUMEN	CRI	COLOR TEMP
LED	4	RL	9	54L	9	30
LED Lighting	4-inch	Commercial Downlight	9 Watt	540 Lumens	CRI 90	3000K



ORDERING

Watts (W)	Ordering Code	Description	CCT (K)	Lumens (Lm)	Size	Equiv. Wattage (W)	Wet/Damp Location	Energy Star
9	7688	LED4RL9-54L930	3000K	540	4"	60	D	•
9	7689	LED4RL9-54L940	4000K	540	4"	60	D	•
9	7690	LED4RL9-54L950	5000K	540	4"	60	D	•
15	7691	LED6RL15-110L930	3000K	1,100	5/6"	120	D	•

ACCESSORIES (Ordered Separately)

Base



P10029 ADP-RLGU24-N
(GU24 Socket Adaptor)

Square Trim



P10176 RTS-4RL9-WH
(Recessed Trim 4" - White)

P10177 RTS-6RL15-WH
(Recessed Trim 6" - White)

Round Trim



P10170 RT-4RL9-BK
(Recessed Trim 4" - Black)

P10173 RT-6RL15-BK
(Recessed Trim 6" - Black)



P10171 RT-4RL9-CH
(Recessed Trim 4" - Chrome)

P10174 RT-6RL15-CH
(Recessed Trim 6" - Chrome)




P10172 RT-4RL9-CH-WH
(Recessed Trim 4" - Chrome White)


P10175 RT-6RL15-CH-WH
(Recessed Trim 6" - Chrome White)

DIMENSIONS

9W (4-inch)
0.93-lbs




15W (6-inch)
1.19-lbs




PHOTOMETRICS CHART

9W (4-inch)
Energy Star



Illuminance at a Distance			
Beam Angle	Center Beam (fc)	Beam Width	Beam Depth
2.6°	49.6 fc	5.0 ft	5.0 ft
5.2°	12.4 fc	9.9 ft	10.0 ft
7.8°	5.51 fc	14.9 ft	15.0 ft
10.4°	3.10 fc	19.8 ft	20.0 ft
12.9°	1.90 fc	24.8 ft	25.0 ft
15.5°	1.30 fc	29.8 ft	30.0 ft


15W (6-inch)
Energy Star



Illuminance at a Distance			
Beam Angle	Center Beam (fc)	Beam Width	Beam Depth
2.6°	80.7 fc	4.9 ft	5.2 ft
5.2°	20.2 fc	9.9 ft	10.4 ft
7.8°	8.97 fc	14.8 ft	15.6 ft
10.4°	5.05 fc	19.7 ft	20.8 ft
12.9°	3.23 fc	24.7 ft	26.0 ft
15.5°	2.24 fc	29.6 ft	31.2 ft

PACKAGE

Case Qty
10 pcs



Case Qty
20 pcs

