SATCO | NUVO

Project / Job Name:

Location:

Fixture Type:

Notes:



63-402 - 4 Watt 10-Inch LED Under Cabinet; 30K/40K/50K CCT Selectable; White Finish 120 Volt

DAMP LOCATION | 90+ CRI | DIMMABLE | ETL US | FC | RoHS COMPLIANT | CCT SELECTABLE | 50,000 HOURS | 120 VOLT

GENERAL

Company	NUVO
EA Height	0.79
EA Width	1.97
EA Length	10.1
Bulb Included	Integrated
Material	Polycarbonate (PC)
Fixture Type	Under Cabinet
Status	Active
Style	Contemporary
Surge Protection	Built-in-surge protection - 0.5KV
Total Harmonic Distortion	<30%
CCT Selectable	True
Wattage Selectable	False
Finish Family	White
Amps	0.033A
Has Camera	False
IOT Enabled	False
Lens Finish	Frost
Lens Material	Polycarbonate (PC)
Lensed	True
Connectable Units	75
Power Factor	>0.9
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	25W

ELECTRICAL

CCT (Kelvin Temp)	3000K/4000K/5000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	110
Color Temp	Soft White to Natural Light
CRI	90+
Dimming Type	Triac
Operating Frequency	60Hz
Operating Temp	-20C (-4F) to +45C (+113F)
Lumens	250L
Volts	120v
Watts	4W

PHYSICAL

Lamp Base	Integrated
Finish	WHITE
ANSI Base	Integrated
Lamp Type	Integrated LED

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Minimum Installation Area: 13" x 4" x 4"

FEATURES

Flicker Free	False

PACKAGING

UPC	045923630378
Case Cube	0.5635
Case Height	6.9
Case Length	12.6
Case Quantity	48
Case UPC	10045923630375
Case Weight	13.63
Case Width	11.2
EA Cube	0.0091
EA Height	0.79
EA Length	10.1
EA Quantity	1
EA Weight	0.22
EA Width	1.97
Inner Cube	0.0725
Inner Height	3.54
Inner Length	8.49
Inner Quantity	12
Inner UPC	20045923630372
Inner Weight	2.86
Inner Width	4.17
Pack Type	Box
Web Height	0.78
Web Length	10.0
Web Width	0.7

COMPLIANCE

ADA Compliant	False
CA Regulations	T20 Exempt - Fixtures Not Regulated
CA Prop 65	Lead
CA Status	Lawful for sale in California
FCC Compliant	True
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cETLus - Listed
CA Compliance Text	Lawful for sale
Title 20	Exempt
T24 Compliant	False

© Satco Products, Inc.
All rights reserved 2025