Project / Job Name:

Location:

Fixture Type:

Notes:



65-981 - 10 Inch LED Field Selectable Canopy Fixture; 45/60/70 Watts; 3K/4K/5K CCT

WET LOCATION · DIMMABLE · FC · RoHS COMPLIANT · CCT SELECTABLE · 50,000 HOURS · IP 65 · 0-10V DIMMING

GENERAL

Company	NUVO
EA Height	11.61
EA Width	5.51
EA Length	11.89
Bulb Included	Integrated
Dimmable Text	0-10V Dimming
Material	Die-cast Aluminum
Fixture Type	Canopy
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 4KV
Total Harmonic Distortion	9.50%
CCT Selectable	True
Wattage Selectable	True
Finish Family	Bronze
Additional Info	UV stabilized powder coated finish
Amps	0.375-0.162/0.500-0.217/0.583-0.253A
Has Camera	False
IOT Enabled	False
Lens Finish	Clear
Lens Material	Polycarbonate (PC)
Photo Cell	No
Power Factor	0.9
SDS Class	LED_Fixture
Indoor Outdoor	Outdoor
Product Technology	LED
Incandescent Equivalent	300W/400W/500W

ELECTRICAL

CCT (Kelvin Temp)	3000K/4000K/5000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	150
Color Temp	Soft White to Natural Light
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-30C (-22F) to +45C (+113F)
HID Equivalent	94W/125W/158W
Lumens	5625L-9450L
Volts	120V-277V
Watts	45W/60W/70W

PHYSICAL

Lamp Base	Integrated
Finish	BRONZE
ANSI Base	Integrated
Lamp Type	Integrated LED
Fixture Shape	Square

ADDITIONAL INFO

Warranty	5-Years

PACKAGING

UPC	045923659478
Case Cube	2.0625
Case Height	12.4
Case Length	23.03
Case Quantity	4
Case UPC	10045923659475
Case Weight	25.02
Case Width	12.48
EA Cube	0.4402
EA Height	11.61
EA Length	11.89
EA Quantity	1
EA Weight	5.29
EA Width	5.51
Inner Cube	0.0
Pack Type	Color Box
Web Height	4.19
Web Length	10.06
Web Width	10.06

COMPLIANCE

Bug Rating	B3-U3-G3
CA Regulations	T20 Exempt - Fixtures Not Regulated
CA Prop 65	Lead
CA Status	Lawful for sale in California
DLC ID	S-TVN5KW
FCC Compliant	True
IP Rating	IP65
Location Rating	Wet
ROHS Compliant	Yes
Safety Listing	cULus - Certified
CA Compliance Text	Lawful for sale
DLC Approved	True
Title 20	Exempt
T24 Compliant	False

© Satco Products, Inc.
All rights reserved 2025