



Because Lighting Speaks Volumes

V2779-5

1-Light Indoor Black Mini Adjustable Track Head with Gimbal Ring

Catalog #:

Type:

Project:

Prepared By:



Description

This indoor black mini adjustable track head features a gimbal ring. Powder-coated paint base finish provides phenomenal long-lasting color and exceptional corrosion/scratch resistance. Compact light fits easily in small spaces. Compatible with Volume Lighting 120V 1-circuit/1-neutral track systems V2702-5 (2 ft. track section), V2704-5 (4 ft. track section), V2706-5 (6 ft. track section), and V2708-5 (8 ft. track section). Also compatible with Volume Lighting 120V 2-circuit/1-neutral track systems V2762-5 (2 ft. track section), V2764-5 (4 ft. track section), V2766-5 (6 ft. track section), and V2768-5 (8 ft. track section). Adjustable track head tilts up to 90° and rotates 355° around vertical axis. Perfect complement to kitchens, living rooms, apartments, studios, stores, bars, restaurants, and many other indoor areas. Suitable for dry locations only. Finished in solid black.

Installation Location	Dry
Light #	1
Watts per Light (W)	50
Total Wattage (W)	50
Light Bulb(s) Included?	No
Recommended Light Bulb Shape	PAR20
Output Power Supply	Class II
Power Factor (Pf)	>.9
THD	<20%
Dimmable?	Yes (TRIAC/ELV, 1% [120V Only])
Base	E26
Input Voltage (Volts)	120V at 50/60 Hz (System Adapter Dependent)
Compliances	RoHS Compliant
Safety Ratings	cETLus Listed
Assembly	No Assembly Required
Accessory 1 (Sold Separately)	L-08PAR20-W LED PAR20 Light Bulb (Energy-Efficient / 8W / 600 Lumens / 3000K / 50,000 Life Rated Hours / 5-Year Warranty / Dimmable)
Accessory 2 (Sold Separately)	V2702-5 2 ft. Black 120V 1-Circuit / 1-Neutral Track System / Section / Rail
Accessory 3 (Sold Separately)	V2704-5 4 ft. Black 120V 1-Circuit / 1-Neutral Track System / Section / Rail
Accessory 4 (Sold Separately)	V2706-5 6 ft. Black 120V 1-Circuit / 1-Neutral Track System / Section / Rail
Accessory 5 (Sold Separately)	V2708-5 8 ft. Black 120V 1-Circuit / 1-Neutral Track System / Section / Rail
Accessory 6 (Sold Separately)	V2762-5 2 ft. Black 120V 2-Circuit / 1-Neutral Track System / Section / Rail
Accessory 7 (Sold Separately)	V2764-5 4 ft. Black 120V 2-Circuit / 1-Neutral Track System / Section / Rail
Accessory 8 (Sold Separately)	V2766-5 6 ft. Black 120V 2-Circuit / 1-Neutral Track System / Section / Rail
Accessory 9 (Sold Separately)	V2768-5 8 ft. Black 120V 2-Circuit / 1-Neutral Track System / Section / Rail

Specifications

Style	Modern
Type of Lighting	Indoor Track Lighting
Product Type	Track Head
Product Subtype	Mini, Gimbal Ring, Adjustable
Height (in.)	6.75
Width (in.)	3.5
Length or Extension/Projection (in.)	3.5
Finish	Black
Main Material	Steel (Powder-Coated Paint Finish)
Light Direction	Adjustable (90° Tilt Around Vertical Axis) (355° Rotation Around Vertical Axis)
Installation/Mounting Position	Downward

At a Glance

- Sturdy, Exquisite Construction
- Perfect Complement to Kitchens, Living Rooms, Apartments, Studios, Stores, Bars, Restaurants, and Many Other Indoor Areas
- Solid Black Finish
- Powder-Coated Hard Surface Provides Long-Lasting Color and Corrosion/Scratch Resistance
- Modern Gimbal Ring Design
- Compact Light Fits Easily in Small Spaces
- Compatible with Volume Lighting 120V 1-Circuit/1-Neutral Track Systems V2702-5 (2 ft. Track Section), V2704-5 (4 ft. Track Section), V2706-5 (6 ft. Track Section), and V2708-5 (8 ft. Track Section)
- Compatible with Volume Lighting 120V 2-Circuit/1-Neutral Track Systems V2762-5 (2 ft. Track Section), V2764-5 (4 ft. Track Section), V2766-5 (6 ft. Track Section), and V2768-5 (8 ft. Track Section)
- Adjustable Track Head (90° Tilt from and 355° Rotation Around Vertical Axis)
- Medium Base (E26) Compatible with Incandescent, Halogen, or LED PAR20 Light Bulbs
- Dimmable (TRIAC/ELV, 1% [120V Only])
- Suitable for Dry Locations Only
- Heat-Resistant Components Withstand Up to 50 Watts
- 1-Light Fixture (Bulb Not Included) (Compatible with Incandescent, Halogen, or LED PAR20 Light Bulbs)
- Individually Inspected for Quality Assurance
- cETLus Rated for Safety