

PROJECT		
TYPE		

OUTDOOR WALL/CEILING FIXTURE S772WF

OUTDOOR DECORATIVE MARLEX®



SPECIFICATIONS

• Wall or Ceiling Mount

Mounting Hardware Included

• Frosted Polycarbonate Diffuser

• Minimum Starting Temp -20°F


• UL Listed for Wet Locations

Composite Construction

WH WHITE

• Black or White

BK BLACK



Wave Lighting's S772WF adds a contemporary look to any outdoor space. Wave Lighting's S772WF is designed for wall or ceiling applications and mounting hardware is included. Options include photocell.



VOLTAGE











LED SOURCE OPTIONS

LIGHTWAVE LED - LR/LT

- 120V, 50/60 Hz
- AC Driver-On-Board Array
- Estimated 50,000 Hrs L_{70}
- Low Flicker (LT models)
- Surge Supression
- Dimmable (see compatible dimmer list)
- High Efficacy LED Light Source
- 3000K or 4000K CCT 80 or 90CRI
- 5 Year Warranty
- Energy Star

LED MULTI-VOLT SYSTEM - L22

- 120-277V, 50/60Hz
- Estimated 50,000 Hrs L_{70}
- 4000K CCT, 80CRI
- 3 Year Warranty

E26 MEDIUM BASE - LE26

- 120V, 50/60Hz
- "Screw-In" Medium Base A19/E26 LED Lamp
- Estimated 15,000 Hrs L_{70}
- Low Flicker (3K models)
- Dimmable (see compatible dimmer list)
- 3000K CCT 90CRI or 4000K CCT 80CRI
- 3 Year Warranty
- Energy Star

GUIDE CODE: S772WF-LR12W-WH-PC

CALL FOR PHOTOMETRIC INFORMATION

ITEM#	DIFFUSER	LIGHT SOURCE	ССТ	COLOR	OPTIONS
F-Frosted Ribbon	POLYCARBONATE	E26 MEDIUM BASE	C -4K	BK -Black	PC-Photocell
	POLYCARBONATE BACK PAN (1) 60W MAX Medium Base LE26-9.5W 800lm (E26 LED Lamp) + *	W -3K WH	WH -White	(120V Lightwave LED only)	
	120V LIGHTWAVE LED				
		ALUMINUM BACK PAN LR12-13W 1000lm 80CRI ★ LR15-15W 1400lm 80CRI ★ LR22-23W 1900lm 80CRI ★ LT12-12W 1040lm 90CRI LT15-16W 1400lm 90CRI LT22-24W 2020lm 90CRI		-	
		120-277V MULTI-VOLT LED			
		L22- 22W 1824Im	4K		

⁺ Lamp included. **★**Energy Star qualified product.