

97594 - GE Ecolux® Biax® T4 - Facilities; Retail Display; Hospitality;

Office; Restaurant; Warehouse

F13DBX/827/ECO4P

Product Photo



GENERAL CHARACTERISTICS

Base Type Pin/Plug-In
Mercury Content 3 mg
Rated Life Hours-nominal 17000 h
Starting Temp (MIN) C-degrees 0 °C
Mercury-Picogrm per mean Im hr
Primary Application Facilities
Retail Displ.

Retail Display Hospitality Office Restaurant Warehouse

Product Technology Compact Fluorescent

Base G24q-1 Bulb Shape A17

PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal755 lmNominal Initial Lumen per Watt69Initial Lumens-nominal900 lmColor Rendering Index-CRI82Color Temperature2700 K

PRODUCT INFORMATION

Product Code 97594

Description F13DBX/827/ECO4P

Alternative Unit Of Measure PACK

DIMENSIONS

Diameter 0.4 in
Nominal Length 5.0 in
Bulb Max Overall Length-MOL 5.0 in

ELECTRICAL CHARACTERISTICS

Equivalent Incandescent Watts 60 W
Current Crest Factor (MAX) 5.25
Rated power (Watts) 13 W

CAUTIONS & WARNINGS

Caution

Lamp may shatter and cause injury if broken

Remove and install by grasping only plastic portion of the lamp.

Remove and install by grasping only plastic portion of the lamp.

NOTES

4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).

