



GE
Lighting

97608 - GE Ecolux® Blax® T4 - Facilities; Retail Display; Hospitality;
Office; Restaurant; Warehouse

F26DBX/835/ECO

Product Photo



GENERAL CHARACTERISTICS

| | |
|---------------------------------|--|
| Base Type | Pin/Plug-In |
| Mercury Content | 3 mg |
| Rated Life Hours-nominal | 10000 h |
| Starting Temp (MIN) C-degrees | -9 °C |
| Mercury-Picogram per mean lm hr | 205.5 |
| Primary Application | Facilities Retail Display Hospitality Office Restaurant Warehouse |
| Product Technology | Compact Fluorescent |
| Base | G24d-3 |
| Bulb Shape | A23 |

PHOTOMETRIC CHARACTERISTICS

| | |
|--------------------------------|---------|
| Mean Lumens nominal | 1460 lm |
| Nominal Initial Lumen per Watt | 66 |
| Initial Lumens-nominal | 1710 lm |
| Color Rendering Index-CRI | 82 |
| Color Temperature | 3500 K |

PRODUCT INFORMATION

| | |
|-----------------------------|----------------|
| Product Code | 97608 |
| Description | F26DBX/835/ECO |
| Alternative Unit Of Measure | PACK |

DIMENSIONS

| | |
|-----------------------------|---------|
| Base Face to Top of Lamp | 5.79 in |
| Nominal Length | 6.7 in |
| Bulb Max Overall Length-MOL | 6.67 in |

ELECTRICAL CHARACTERISTICS

| | |
|--------------------------------|-------|
| Equivalent Incandescent Watts | 100 W |
| Supply Current Freq nominal Hz | 60 Hz |
| Rated power (Watts) | 26 W |

CAUTIONS & WARNINGS

Caution

Lamp may shatter and cause injury if broken

Remove and install by grasping only plastic portion of the lamp.

NOTES

Based on 60Hz reference circuit.

