



GE
Lighting

75952 - GE LFL UltraStart® Electronic Program / Rapid Start Ballast

GE132-MVPS-L

- ☞ A new generation of ultra-efficient Programmed Start ballasts (> 90% efficiency).
- ☞ Extends lamp life in frequently switched applications (> 100,000 on/off cycles)
- ☞ Multi-Voltage Technology handles voltage from 120 to 277V
- ☞ Starting time visually the same as instant start
- ☞ Anti-striation circuitry reduces striations with energy saving lamps

Product Photo



GENERAL CHARACTERISTICS

Ballast Factor	Low-PS (.71)
Ballast Type	Program / Rapid Start
Case Temperature (Max)	70 °C
Enclosure Type	Metal
Line Voltage Regulation (+/-)	10%
Classification (Regulations)	ANSI - C62.41
	cUL Listed
	FCC - CLASS A Non-Consumer
	UL Class P
	UL Listed
	UL Type 1 Outdoor
	UL Type HL
	NEMA Premium®
	Product is compliant with material restriction requirements of RoHS
	A (20-24 decibels)
Sound Rating	Programmed start
Starting Method	Linear Fluorescent
Product Technology	Parallel
Lamp Wiring	Active
Power Factor Correction	

PRODUCT INFORMATION

Product Code	75952
Description	GE132-MVPS-L
Alternative Unit Of Measure	EACH
Standard Package Quantity	10
Ean UPC	043168759526
Standard Package GTIN	00043168759526
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	10
Sales Unit	Each
UCC	043168759526
Alternative Unit Of Measure	CASE

DIMENSIONS

Weight	1.65 lb
Remote Mount Distance	18.0 ft

Case Dimensions

Length	9.5in
Width	1.7in
Height	1.18in

Mounting Dimensions

Mount Length	8.89in
Mount Width	1.13in
Mount Slot	0.312in

Lead Color	Qty	Exit	Length (1 in.)
Black	1	Left	25in
White	1	Left	25in
Blue	2	Right	33in
Yellow	2	Right	48in

ELECTRICAL CHARACTERISTICS

Supply Current Frequency<Min>	50
-------------------------------	----

SAFETY & PERFORMANCE

- ☞ ANSI_C62
- ☞ cUL_Listed
- ☞ FCC_CS_NCons
- ☞ UL_Cls_P
- ☞ UL_Listed
- ☞ UL_Type1_Out
- ☞ UL_Type_HL
- ☞ NEMA_Pre
- ☞ Pro_comp_res_req

SPECIFICATIONS BY LAMP & WATTAGE

Lamp	# of Lamps	Line Volts	System Watts	Nom. Line Current	System Ballast Factor	Ballast Efficacy Factor	Power Factor% (>=)	Crest Factor (<=)	THD% (<=)	Min. Starting Temp (F/ C)
F17T8	1	120	14	0.12	0.75	5	0.99	1.7	10	0
F25T12	1	120	20	0.18	0.72	4	0.99	1.7	10	0
F25T12	1	277	21	0.08	0.72	3	0.94	1.7	10	0
F17T8	1	277	15	0.06	0.75	5	0.89	1.7	10	0
F25T8	1	120	19	0.17	0.73	4	0.99	1.7	10	0
F25T8	1	277	20	0.08	0.73	4	0.93	1.7	10	0
F28T8	1	277	22	0.09	0.71	3	0.94	1.7	10	50
F28T8	1	120	22	0.19	0.71	3	0.99	1.7	10	50
F32T8/WM	1	120	23	0.2	0.71	3	0.99	1.7	10	50
F32T8/WM	1	277	23	0.09	0.71	3	0.95	1.7	10	50
F32T8	1	120	25	0.22	0.72	3	0.99	1.7	10	0
F32T8	1	277	25	0.1	0.72	3	0.96	1.7	10	0
F40T8	1	120	29	0.25	0.71	2	0.99	1.7	10	0
F40T8	1	277	29	0.11	0.71	2	0.97	1.7	10	0
F25T8/WM	1	120	17	0.14	0.71	4	1.0	1.7	10	0
F25T8/WM	1	277	17	0.07	0.71	4	0.92	1.7	10	0
F17T8/WM	1	120	13	0.11	0.72	5	0.99	1.7	10	0
F17T8/WM	1	277	13	0.06	0.72	5	0.88	1.7	10	0
F32T8/25W	1	120	20	0.18	0.71	4	0.99	1.7	10	50
F32T8/25W	1	277	21	0.08	0.71	3	0.94	1.7	10	50
FE15T8	1	277	13	0.1	0.66	5	0.86	1.7	10	0
F29T8	1	120	23	0.19	0.71		1.0			
F29T8	1	277	23	0.09	0.71		0.95			
F31T8	1	120	24	0.2	0.71		1.0			
F31T8	1	277	24	0.09	0.71		0.96			
F26T8	1	120	20	0.17	0.68		1.0			
F26T8	1	277	21	0.08	0.68		0.94			

