



PL-C Cluster 2-Pin Base

PL-C 26W/827/2P/ALTO 10PK

Philips Linear Compact Fluorescent Lamps offer designers, specifiers and end-users new levels of efficiencies and versatility in sizes, configurations and application possibilities. With so many elegant fixtures available to complement their small size, high light output and advanced technology, Philips Energy Advantage lamps are fast becoming the preferred choice when maximum efficiency and sleek design solutions are required.

Product data

General Information			
Cap-Base	G24D-3 [G24d-3]	LLMF 6000 h Rated	83 %
Life To 10% Failures (Nom)	6500 h	LLMF 8000 h Rated	81 %
Life To 50% Failures (Nom)	10000 h		
LSF 2000 h Rated	99 %	Operating and Electrical	
LSF 4000 h Rated	98 %	Power (Rated) (Nom)	26.5 W
LSF 6000 h Rated	92 %	Lamp Current (Nom)	0.335 A
LSF 8000 h Rated	78 %		
Light Technical		Temperature	
Color Code	827 [CCT of 2700K]	Design Temperature (Nom)	28 °C
Initial lumen (Nom)	1800 lm		
Luminous Flux (Rated) (Nom)	1800 lm	Controls and Dimming	
Color Designation	Incandescent White	Dimmable	No
Chromaticity Coordinate X (Nom)	463		
Chromaticity Coordinate Y (Nom)	420	Mechanical and Housing	
Correlated Color Temperature (Nom)	2700 K	Cap-Base Information	2P
Luminous Efficacy (rated) (Nom)	68 lm/W		
Color Rendering Index (Nom)	82	Approval and Application	
LLMF 2000 h Rated	92 %	Energy Efficiency Label (EEL)	B
LLMF 4000 h Rated	87 %	Mercury (Hg) Content (Nom)	1.4 mg
		Energy Consumption kWh/1000 h	32 kWh


PL-C Cluster 2-Pin Base

Product Data

Order product name	PL-C 26W/827/2P/ALTO 10PK
EAN/UPC - Product	046677109554
Order code	383216
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10

Material Nr. (12NC)	927906182730
Net Weight (Piece)	64.300 g
ILCOS Code	F5Q-26/27/1B-I-G24d=3

Dimensional drawing



Product	D	D1	A	B	C
PL-C 26W/827/2P/ALTO 10PK	27.1 mm	27.1 mm	130.5 mm	149.0 mm	171.4 mm

PL-C 26W/827/2P

