

Features & Benefits

- No rewiring needed
- Works with fluorescent electronic T5 ballast
- Long life
- High CRI
- Instant on, no delay
- Convenient and quick installation
- Utilizes existing T5 sockets
- No Mercury, No UV
- Compatible with controls and sensors
- Works in cold temperature applications
-
-
-



* EMERGENCY BALLAST RESTRICTIONS




RetroFlex™
LED T5HO LAMP • Simplicity.
Commercial Grade LED T5 Lamp

Specification Data

Order Code	Length	Lamp Wattage	System Wattage	CCT	Initial Lumens	CRI	Beam Angle	Lamp Efficacy	System Efficacy	Life	DLC
L48T5HO/835/24G-EB-AC	48"	25W	28	3500K	3200	83	240°	128	115	50000	Yes
L48T5HO/840/24G-EB-AC	48"	25W	28	4000K	3200	83	240°	128	115	50000	Yes
L48T5HO/850/24G-EB-AC	48"	25W	28	5000K	3200	83	240°	128	115	50000	Yes

Wiring Diagram



* Not compatible with products equipped with battery backup and/or emergency ballasts.

* Please refer to "Ballast Compatibility List" on Related Downloads.

Specification data is based on tests performed in a controlled environment and represents relative performance. Actual performance can vary depending on operating conditions. Application and performance data subject to change without notice. All specifications are nominal unless noted otherwise.