

Features & Benefits

- Internal Driver
- Smooth, Consistent Light
- UL for Safety
- No UV, No Mercury
- Long Life
- High CRI
- Instant on, no delay or warm up time
- Convenient and quick installation
- Utilizes non-shunted(rapid start) sockets
- Compatible with controls and sensors
- Works in cold temperature applications
- 5 Year Warranty
- Made of Glass



Commercial Grade **LED T8 Lamp**



Flex™

Internal Driver **LED T8 Lamp**

Specification Data

Model No.	Length	Lamp Wattage	Input Voltage	CCT	Initial Lumens	CRI	Beam Angle	LPW	Life	Operating Temp.
L48T8/835/18G-ID 48	18		120-277	3500	2200	83	325	115	50000	-20 ~ 40
L48T8/840/18G-ID 48	18		120-277	4000	2200	83	325	115	50000	-20 ~ 40
L48T8/850/18G-ID 48	18		120-277	5000	2200	83	325	115	50000	-20 ~ 40

Ordering Information

EXAMPLE: **L48T8/840/14G-ID DE**

L

Manufacturer's Code

48

Normal Length
48=48"

T8

Lamp Shape
T8=T8

8

CRI
8=>80

40

CCT
50=5000K
40=4000K
35=3500K

14 G


Wattage
14G-14W

-

ID

Internal Driver

Wiring diagram



Espen Technology, Inc. | 12257 Florence Avenue | Santa Fe Springs, CA 90670 | Phone: (562) 529-2938 | Fax: (562) 529-2978
Toll-free: (866) 933-7736 | Email: info@espentech.com | www.espentech.com