



Haloxen. MR11 & MR16

Halco
LIGHTING TECHNOLOGIES

Technical Data

- 3100K and 3150K
- Aluminized Reflector
- Protective glass lens for operation in open or enclosed fixtures
- Integrated UV protection
- Axial filament for precise light distribution
- High lumen maintenance - over 90% throughout lamp life

Long Life

- 5,000 and 10,000 Hours Average Rated Life

Benefits

- White light
- No color shift
- Greatly reduces fading caused by UV exposure
- Long life - as much as twice the rated life of standard MR16 lamps
- Decrease in labor costs associated with re-lamping

Haloxen lamps provide improved efficiency and 5,000 to 10,000 hours rated average life.

Applications

- Retail
- Display/Accent lighting
- General lighting

where there's light, there's halco®

Contact your account representative at 800.677.3334 for pricing, orders and technical support.

Visit us at halcolighting.com

Haloxen. MR11 & MR16

Catalog Number: _____ Type: _____
 Project: _____
 Comments: _____ Date: _____
 Prepared By: _____

HALOXEN

| Bulb Type | Watts | Base | Product # | Product Code | Description | Pkg Qty | Volts | Color Temp | CBCP | Life | Filament Design | MOL (Inc) | Beam Spread |
|-------------------|-------|-------|-----------|------------------|----------------------|---------|-------|------------|-------|-------|-----------------|-----------|-------------|
| MR11 Lamps | | | | | | | | | | | | | |
| MR11 | 20 | GU4 | 107922 | MR11FTB/L/HX | Narrow Spot w/ Lens | 10/200 | 12 | 3100 | 4100 | 10000 | C-8 | 1.38" | 10° |
| MR11 | 20 | GU4 | 107924 | MR11FTC/L/HX | Medium Flood w/Lens | 10/200 | 12 | 3100 | 1750 | 10000 | C-8 | 1.38" | 20° |
| MR11 | 20 | GU4 | 107926 | MR11FTD/L/HX | Flood w/Lens | 10/200 | 12 | 3100 | 700 | 10000 | C-8 | 1.38" | 30° |
| MR11 | 35 | GU4 | 107928 | MR11FTF/L/HX | Medium Flood w/ Lens | 10/200 | 12 | 3100 | 3000 | 10000 | C-8 | 1.38" | 20° |
| MR11 | 35 | GU4 | 107930 | MR11FTH/L/HX | Flood w/Lens | 10/200 | 12 | 3100 | 1500 | 10000 | C-8 | 1.38" | 30° |
| MR16 Lamps | | | | | | | | | | | | | |
| MR16 | 16 | GU5.3 | 70754 | MR16SP20/L/16HX | Spot w/Lens | 10/100 | 12 | 3100 | 3600 | 5000 | C-8 | 1.77" | 10° |
| MR16 | 16 | GU5.3 | 70753 | MR16NFL20/L/16HX | Narrow Flood w/Lens | 10/100 | 12 | 3100 | 1100 | 5000 | C-8 | 1.77" | 25° |
| MR16 | 16 | GU5.3 | 70752 | MR16FL20/L/16HX | Flood w/Lens | 10/100 | 12 | 3100 | 650 | 5000 | C-8 | 1.77" | 36° |
| MR16 | 16 | GU5.3 | 70755 | MR16WFL20/L/16HX | Wide Flood w/Lens | 10/100 | 12 | 3100 | 400 | 5000 | C-8 | 1.77" | 60° |
| MR16 | 20 | GU5.3 | 107526 | MR16BAB/L/HX | Flood w/Lens | 10/100 | 12 | 3100 | 700 | 10000 | C-8 | 1.77" | 38° |
| MR16 | 20 | GU5.3 | 107932 | MR16ESX/L/HX | Narrow Spot w/Lens | 10/100 | 12 | 3100 | 4100 | 10000 | C-8 | 1.77" | 10° |
| MR16 | 20 | GU5.3 | 107942 | MR16WFL20/L/HX | Wide Flood w/Lens | 10/100 | 12 | 3100 | 400 | 10000 | C-8 | 1.77" | 60° |
| MR16 | 26 | GU5.3 | 70758 | MR16SP35/L/26HX | Spot w/Lens | 10/100 | 12 | 3100 | 6500 | 5000 | C-8 | 1.77" | 10° |
| MR16 | 26 | GU5.3 | 70757 | MR16NFP35/L/26HX | Narrow Flood w/Lens | 10/100 | 12 | 3100 | 3150 | 5000 | C-8 | 1.77" | 25° |
| MR16 | 26 | GU5.3 | 70756 | MR16FL35/L/26HX | Flood w/Lens | 10/100 | 12 | 3100 | 1250 | 5000 | C-8 | 1.77" | 36° |
| MR16 | 26 | GU5.3 | 70759 | MR16WFL35/L/26HX | Wide Flood w/Lens | 10/100 | 12 | 3100 | 800 | 5000 | C-8 | 1.77" | 60° |
| MR16 | 35 | GU5.3 | 107518 | MR16FMW/L/HX | Flood w/Lens | 10/100 | 12 | 3100 | 1250 | 10000 | C-8 | 1.77" | 38° |
| MR16 | 35 | GU5.3 | 107938 | MR16FRA/L/HX | Spot w/Lens | 10/100 | 12 | 3100 | 3500 | 10000 | C-8 | 1.77" | 20° |
| MR16 | 35 | GU5.3 | 70720 | MR16WFL35/L/HX | Wide Flood w/Lens | 10/100 | 12 | 3100 | 750 | 10000 | C-8 | 1.77" | 60° |
| MR16 | 37 | GU5.3 | 70736 | MR16FL50/L/37HX | Flood w/Lens | 10/100 | 12 | 3100 | 2200 | 5000 | C-8 | 1.77" | 36° |
| MR16 | 37 | GU5.3 | 70737 | MR16NFL50/L/37HX | Narrow Flood w/Lens | 10/100 | 12 | 3100 | 4400 | 5000 | C-8 | 1.77" | 25° |
| MR16 | 37 | GU5.3 | 70738 | MR16SP50/L/37HX | Spot w/Lens | 10/100 | 12 | 3100 | 12500 | 5000 | C-8 | 1.77" | 10° |
| MR16 | 37 | GU5.3 | 70739 | MR16WFL/L/37HX | Wide Flood w/Lens | 10/100 | 12 | 3100 | 1100 | 5000 | C-8 | 1.77" | 60° |
| MR16 | 50 | GU5.3 | 107514 | MR16EXN/L/HX | Flood w/Lens | 10/100 | 12 | 3150 | 1700 | 10000 | C-8 | 1.77" | 38° |
| MR16 | 50 | GU5.3 | 107934 | MR16EXT/L/HX | Spot w/Lens | 10/100 | 12 | 3150 | 10000 | 10000 | C-8 | 1.77" | 12° |
| MR16 | 50 | GU5.3 | 107936 | MR16EXZ/L/HX | Narrow Flood w/Lens | 10/100 | 12 | 3150 | 4400 | 10000 | C-8 | 1.77" | 24° |
| MR16 | 50 | GU5.3 | 107524 | MR16FNV/L/HX | Wide Flood w/Lens | 10/100 | 12 | 3150 | 1000 | 10000 | C-8 | 1.77" | 60° |
| MR16 | 57 | GU5.3 | 70760 | MR16FL75/L/57HX | Flood w/Lens | 10/100 | 12 | 3100 | 2400 | 5000 | C-8 | 1.77" | 36° |



Atlanta | Carlstadt | Cleveland | Los Angeles | Houston | Phoenix