

LED



844 SERIES



84461
FROSTED | WHITE



84491
CLEAR | WHITE



84465
FROSTED | BLACK




84495
CLEAR | BLACK

STANDARD SPECIFICATIONS

Housing	Impact Resistant Polycarbonate (Specify Finish) UV Stabilized Acrylic (Specify Type) 120V Wet Location Listed LED
Lens	
Voltage	
Certification	
Light Source	

REPLACEMENT PARTS

- LENS-8446** | (4) UV Stabilized Frosted Acrylic Panels
- LENS-8449** | (4) UV Stabilized Clear Acrylic Panels



PHOTOCELL / ADAPTER



PCA5

PIER MOUNTS



PMB

PMW

PRODUCT FAMILY	LENS TYPE	FINISH	MODEL	: 95H F9G / C DHCBD
844				



6 - Frosted

9 - Clear

1 - White

5 - Black

10LEDGU

120V, 60Hz Electronic Dimmable
9 Watts, 800 Lumens, GU24 Base
Options: 27K, 30K, 40K, PCA1, PCA5, PMB, PMW

12LEDGU

120V, 60Hz Electronic Dimmable
11 Watts, 1100 Lumens, GU24 Base
Options: 27K, 30K, 40K, PCA1, PCA5, PMB, PMW

13LED-120

120V, 50/60Hz Electronic, 120V Dimmable
13 Watts, 900 Lumens, >80CRI
Options: 30K, 40K, PCA1, PCA5, PMB, PMW

17LEDGU

120V, 60Hz Electronic Dimmable
15 Watts, 1600 Lumens, GU24 Base
Options: 27K, 30K, 40K, PCA1, PCA5, PMB, PMW

OPTION LEGEND

27K	2700 Kelvin Warm White Light Temperature
30K	3000 Kelvin Warm White Light Temperature
40K	4000 Kelvin Cool White Light Temperature
PCA1	Photocell w/Adapter White
PCA5	Photocell w/ Adapter Black
PMB	Pier Mount Black
PMW	Pier Mount White