

LED OMNIDIRECTIONAL A-LAMP
A19 GEN 5 SERIES



6W, 9W & 11W



15W



GU24 Base



PRODUCT DESCRIPTION:

MaxLite's LED Omnidirectional A-Line lamp replicate true A19 incandescents. They are suited to a wide variety of residential and commercial applications, including pendants, wall sconces and table and floor lamps.

FEATURES:

- 6W, 480lm, 40W Inc. replacement
- 9W, 800lm, 60W Inc. replacement
- 11W, 1100lm, 75W Inc. replacement
- 15W, 1600lm, 100W Inc. replacement
- Dimmable down to 10 percent
- Power factor: ≥ 0.90
- 25,000 hour life (L70 standards)
- CRI: ≥ 80
- ENERGY STAR Certified
- Available in E26 and GU24 base
- Suitable for dry and damp locations
- Not for use in fully enclosed luminaires
- Five year limited warranty

APPLICATIONS

- Pendants
- Table and floor lamps
- Sconces

ORDERING:

MODEL SELECTION (Full list of order codes on pg. 2)		Typical order example: 9A19DLED27/G5		
FAMILY	BASE	DIMMABILITY	CCT	GENERATION
6A19= 6 watts, A19 9A19= 9 watts, A19 11A19= 11 watts, A19 15A19= 15 watts, A19	(OMIT)= E26 GU= GU24	DLED= Dimmable	27= 2700K 30= 3000K 40= 4000K	/G5= Generation 5

NOTES:

1. 6A19DLED27/G5 is available in bulk pack (50pcs)
2. 9A19DLED27/G5 is available in 4-Packs and bulk pack (50pcs)
3. 11A19DLED27/G5 is available in bulk pack (50pcs)

SPECIFICATIONS:

		6A19DLEDxx/G5	9A19DLEDxx/G5	11A19DLEDxx/G5	15A19DLEDxx/G5
ITEM	SPECIFICATION	DETAILS			
GENERAL PERFORMANCE	Power Consumption	6W	9W	11W	15W
	Lumens Delivered	480	800	1100	1600
	Efficacy (lm/w)	80	88	100	106
	CRI	≥80			
	Color Temperature (CCT)	2700K, 3000K, 4000K			
	Lumen Maintenance (L70)	25,000 Hours			
ELECTRICAL	Power Factor	≥0.9			
	Input Voltage	120V			
PHYSICAL	Base Type	E26			
	Operating Temperature	-4°F - 104°F			
CERTIFICATION	Certification	Energy Star 2.0, UL Listed, RoHS Compliant			
	Environment	Dry, Damp			
	Warranty	5 Year Limited			

Lighting layouts and spacing criteria available upon request

ORDERING:

ORDER CODE	MODEL	ENERGY STAR	WATTS	EQUIVALENCY	DELIVER LUMENS	EFFICACY (lm/W)	CRI	CCT	DIMENSIONS (W" x MOL")
E26 Base									
107589	6A19DLED27/G5	★	6	40W Inc.	480	80	80	2700K	2.36" x 4.25"
107590	6A19DLED27/G5/BP	★	6	40W Inc.	480	80	80	2700K	
107718	6A19DLED30/G5	★	6	40W Inc.	480	80	80	3000K	
1409250	6A19DLED40/G5	★	6	40W Inc.	480	80	80	4000K	
107584	9A19DLED27/G5	★	9	60W Inc.	800	88	82	2700K	
107809	9A19DLED27/G5/4P	★	9	60W Inc.	800	88	82	2700K	
107583	9A19DLED27/G5/BP	★	9	60W Inc.	800	88	82	2700K	
107717	9A19DLED30/G5	★	9	60W Inc.	800	88	82	3000K	
1409242	9A19DLED40/G5	★	9	60W Inc.	800	88	82	4000K	
107585	11A19DLED27/G5	★	11	75W Inc.	1100	100	83	2700K	
107586	11A19DLED27/G5/BP	★	11	75W Inc.	1100	100	83	2700K	
107719	11A19DLED30/G5	★	11	75W Inc.	1100	100	83	3000K	
1408351	11A19DLED40/G5	★	11	75W Inc.	1100	100	83	4000K	
107720	15A19DLED27/G5	★	15	100W Inc.	1600	106	84	2700K	
107721	15A19DLED30/G5	★	15	100W Inc.	1600	106	84	3000K	
1409244	15A19DLED40/G5	★	15	100W Inc.	1600	106	84	4000K	

★ ENERGY STAR Certified

Specifications are subject to change without notice.

ORDER CODE	MODEL	ENERGY STAR	WATTS	EQUIVALENCY	DELIVER LUMENS	EFFICACY (lm/W)	CRI	CCT	DIMENSIONS (W" x MOL")
GU24 Base									
1409336	6A19GUDLED27/G5	★	6	40W Inc.	480	80	80	2700K	2.36" x 4.21"
1409407	6A19GUDLED30/G5	★	6	40W Inc.	480	80	80	3000K	
1409337	6A19GUDLED40/G5	★	6	40W Inc.	480	80	80	4000K	
1409408	9A19GUDLED27/G5	★	9	60W Inc.	800	89	80	2700K	
1409338	9A19GUDLED30/G5	★	9	60W Inc.	800	89	80	3000K	
1409243	9A19GUDLED40/G5	★	9	60W Inc.	800	89	80	4000K	
1409339	11A19GUDLED27/G5	★	11	75W Inc.	1100	100	80	2700K	
1409340	11A19GUDLED30/G5	★	11	75W Inc.	1100	100	80	3000K	
1409019	11A19GUDLED40/G5	★	11	75W Inc.	1100	100	80	4000K	
1409341	15A19GUDLED27/G5	★	15	100W Inc.	1600	106	83	2700K	2.36" x 4.61"
1409342	15A19GUDLED30/G5	★	15	100W Inc.	1600	106	83	3000K	
1409245	15A19GUDLED40/G5	★	15	100W Inc.	1600	106	83	4000K	

★ ENERGY STAR Certified

COMPATIBLE DIMMERS (6A19DLEDXX/G5):

MANUFACTURE	DIMMER MODEL
AH	SDM/600
	SDM3/1000
ALMOND	LUXDM600-12
CTL	DM600-12-3
GE	18024
LEVITON	603-6631-A
	6631
	6631-A
	6631-LA
	6672
	6683
	6683-10Z
	IPI06-1LZ
	IPI10-1LZ
	IPL06
LUTRON	AYCL-153P-WH
	AYCL-153PH
	DVCL-153P-WH
	DWCL-153PH-WHC
	S-603PH-WH
	SCL-153PH-WH
	TGCL-153PH-WH
MAAXIMA	MEW-DM600

COMPATIBLE DIMMERS (9A19DLEDXX/G5):

MANUFACTURE	DIMMER MODEL
AH	SDM/600
	SDM3/1000
ALMOND	LUXDM600-12
CTL	DM600-12-3
GE	18024
LEVITON	6631
	6672
	6683
	603-6631-A
	6631-A
	6683-10Z
	IPI06-1LZ
	IPI10-1LZ
	IPL06
LUTRON	AYCL-153P-WH
	AYCL-153PH
	DVCL-153P-WH
	DWCL-153PH-WHC
	S-603PH-WH
	SCL-153PH-WH
	TGCL-153PH-WH
MAAXIMA	MEW-DM600

COMPATIBLE DIMMERS (11A19DLEDXX/G5):

MANUFACTURE	DIMMER MODEL
AH	SDM/600
	SDM3/1000
ALMOND	LUXDM600-12
CTL	DM600-12-3
GE	18024
LEVITON	6631
	6672
	6683
	603-6631-A
	6631-A
	6631-LA
	6683-10Z
	IPI06-1LZ
	IPI10-1LZ
	IPL06
LUTRON	AYCL-153P-WH
	AYCL-153PH
	DVCL-153P-WH
	DVWCL-153PH-WHC
	S-603PH-WH
	SCL-153PH-WH
	TGCL-153PH-WH
MAAXIMA	MEW-DM600

COMPATIBLE DIMMERS (15A19DLEDXX/G5):

MANUFACTURE	DIMMER MODEL
AH	SDM/600
	SDM3/1000
ALMOND	LUXDM600-12
CTL	DM600-12-3
GE	18024
LEVITON	6631
	603-6631-A
	6631-A
	6631-LA
LUTRON	AYCL-153P-WH
	AYCL-153PH
	D-600PH-DK
	D-600R-IV
	DV-600P-WH
	DV-600PH-WH
	DV-603P
	DV-603PH-WH
	DV-603PR
	DVW-600PH-WH
	MACL-153M-WH
	MACL-153MLH-WH
	MACL-153MR-WH
	MACL-153MH-WH
	S-600
	S-600-AL
	S-600P-WH
S-603PH-WH	
TG-600PH-IV	
TGCL-153PH-WH	

Specifications are subject to change without notice.