# **Light Pole Accessories**



# Size: 4" (4" × 4"), 5" (5" × 5")

| SQUARE EXTERNAL MOUNT HORIZONTAL TENON  |  | To mount 2/3/4 fixtures on an existing pole  |   |
|---|--|--|---|
| 45° (1140mm)<br>45° (1140mm)<br>47° (120mm)<br>47° (120mm)<br>1.24° (115mm)<br> | Low Profile Bullhorn with 3 Tenons<br>WSD-VTS4R-3T-D<br>MAX EPA: 1.6<br>Finish: Dark Bronze<br>The Bracket is designed to mount over<br>2-3/8" O.D. vertical tenon.  | 20.5" (320mm)<br>4.7" (120mm)/<br>4.7" (120mm)/<br>24.4" (624.38mm)<br>24.4" (624.38mm)  | Low Profile Bullhorn with 2 Tenons<br>WSD-VTS4R-2T-D<br>MAX EPA: 1.0<br>Finish: Dark Bronze<br>The Bracket is designed to mount over<br>2-3/8" O.D. vertical tenon.   |
| HOLE (DATE)   | Triple 120° Horizontal Tenon Adapter<br>WSD-QT120-3T-D<br>MAX EPA: 1.4<br>Finish: Dark Bronze<br>The Bracket is designed to mount over<br>2-3/8" O.D. vertical tenon.  |  | Quad 90° Horizontal Tenon Adapter<br>WSD-VTS4R-3T-D<br>MAX EPA: 1.6<br>Finish: Dark Bronze<br>The Bracket is designed to mount over<br>2-3/8" O.D. vertical tenon.  |
| WALL BRACKET • Attaches to a  | ny flat surface • Provides wiring access   | MID-POLE TENON BRACKET   |   |
| ø2.36"<br>7"<br>7.8"<br>7"  | 90° Wall Mount Bracket with 2-3/8" 0.D. Tenon<br>WSD-ADP2.5-90-D<br>MAX EPA: 0.6<br>Finish: Dark Bronze<br>The 90° wall mount bracket with 2-3/8"<br>tenon attaches flood and area fixtures to<br>almost any surface: wall, roof, or wood<br>pole. Provides wiring access and a built-in<br>2-3/8" O.D. tenon to mount a fixture with<br>our adjustable slip-fitter. Suggested 3/8"<br>diameter bolts for mounting.        | 8"<br>4.92"<br>3.75"<br>5.6"   | 2-3/8" 0D Horizontal Tenon Mid-Pole Bracket<br>WSD-ADP2.5-D<br>MAX EPA: 0.3<br>Finish: Dark Bronze<br>2-3/8" OD Horizontal Tenon Mid-Pole<br>Bracket is designed to mount light fixture<br>that is equipped with a adjustable slip-fit-<br>ter onto a 2-3/8" OD horizontal tenon.   |
| 3.9' (99mm)<br>3.9' (99mm)<br>R2' 4-09 0.16' (4mm)                              | 180° Wall Mount Bracket with 2-3/8" 0.D. Tenon<br>WSD-ADP2.5-180L3.9-D<br>MAX EPA: 0.5<br>Finish: Dark Bronze<br>The 180° wall mount bracket with 2-3/8"<br>tenon attaches flood and area fixtures to<br>almost any surface: wall, roof, or wood<br>pole. Provides wiring access and a built-in<br>2-3/8" O.D. tenon to mount a fixture with<br>our adjustable slip-fitter. Suggested 3/8"<br>diameter bolts for mounting. | D2 ATTRINUT<br>T2 I TIMANY<br>I TIMANY<br>I S CHI 2 ANN<br>I S CHI 2 ANN | 2-3/8" 0D Horizontal Tenon Arc Adapter<br>WSD-ADP2.5-BAR5-D<br>MAX EPA: 0.3<br>Finish: Dark Bronze<br>For use with Round, non-tapered steel ar<br>aluminum poles.2-3/8" OD Horizontal<br>Tenon Mid-Pole Bracket is designed to<br>mount light fixture that is equipped with a<br>adjustable slip-fitter onto a 2-3/8" OD<br>horizontal tenon. |
| POLE BRACKET • For mounting   | one fixture on an existing pole  |  |   |
| ¢2.38"<br>4.33"<br>4.33"<br>4.6"  | 4" Square Pole Mount with 2-3/8" 0.D. Tenon<br>WSD-VTS4-D<br>MAX EPA: 0.3<br>Finish: Dark Bronze<br>For use with square, non-tapered steel and<br>aluminum poles. Furnished with four 5/16"<br>hex head stainless-steel bolts. Vertical<br>tenon measures 2-3/8" O.D. and is made of<br>steel tubing.  | \$2.36<br>\$3.15"<br>\$3.46"<br>\$4.8"   | <b>3" Round Pole Mount with 2-3/8" 0.D. Tenon</b><br><b>WSD-VT3-D</b><br>MAX EPA: 0.3<br>Finish: Dark Bronze<br>For use with round, non-tapered steel and<br>aluminum poles. Furnished with four 3/8"<br>hex head stainless-steel bolts. Vertical<br>tenon measures 2-3/8" O.D.   |
| ¢2.38"<br>5"<br>4"<br>4"  | 5" Square Pole Mount with 2-3/8" 0.D. Tenon<br>WSD-VTS5-D<br>MAX EPA: 0.3<br>Finish: Dark Bronze<br>For use with square, non-tapered steel and<br>aluminum poles. Furnished with four 5/16"<br>hex head stainless-steel bolts. Vertical ten-<br>on measures 2-3/8" O.D., and is made of<br>steel tubing.   | °2.36"<br>4"<br>4"<br>4.8"   | 4" Round Pole Mount with 2-3/8" 0.D. Tenon<br>WSD-VT4-D<br>MAX EPA: 0.3<br>Finish: Dark Bronze<br>For use with round, non-tapered steel an<br>aluminum poles. Furnished with four 3/8"<br>hex head stainless-steel bolts. Vertical<br>tenon measures 2-3/8" O.D.  |
| 02.36<br>02.13<br>4-M8<br>05.27<br>05.51  | 5" Round Pole Mount with 2-3/8" 0.D. Tenon<br>WSD-VT5-D<br>MAX EPA: 0.3<br>Finish: Dark Bronze<br>For use with round, non-tapered steel and<br>aluminum poles. Furnished with four 3/8"<br>hex head stainless-steel bolts. Vertical ten-<br>on measures 2-3/8" O.D., and is made of<br>steel tubing.   |  | 1/2" Round Pole Mount with 2-3/8" 0.D. Tenon<br>WSD-TADP2.5-1/2-D<br>MAX EPA: 0.3<br>Finish: Dark Bronze<br>For use with Round, non-tapered steel ar<br>aluminum poles.Vertical tenon measures<br>2-3/8" O.D., and is made of aluminum<br>tubing.   |

## www.lightbulbsurplus.com | sales@lightbulbsurplus.com

# **Light Pole Accessories**



## Size: 4" (4" × 4"), 5" (5" × 5")

| 10.23"<br>02.36"<br>02.7"<br>03"   | Double 90° Horizontal Tenon Adapter<br>WSD-SB2.5TW90-D<br>MAX EPA: 0.6<br>Finish: Dark Bronze<br>The Bracket is designed to mount over<br>2-3/8" (60mm) O.D. vertical tenon. Two<br>fixtures can be mounted to the Round<br>External Mount Horizontal Tenon and<br>adjusted horizontally.  | 10"<br>2.6"<br>2.6"<br>02.667"<br>02.667"<br>02.667"   | Triple 120° Horizontal Tenon Adapter<br>WSD-SB2.5TR120-D<br>MAX EPA: 0.7<br>Finish: Dark Bronze<br>The Bracket is designed to mount ove<br>2-3/8" (60mm) O.D. vertical tenon. Th<br>fixtures can be mounted to the Round<br>External Mount Horizontal Tenon and<br>adjusted horizontally.   |
|--|--|--|---|
| 10.23"<br>02.36"<br>02.7"<br>02.7"<br>03"  | Double 180° Horizontal Tenon Adapter<br>WSD-SB2.5TW180-D<br>MAX EPA: 0.4<br>Finish: Dark Bronze<br>The Bracket is designed to mount over<br>2-3/8" (60mm) O.D. vertical tenon. Two<br>fixtures can be mounted to the Round<br>External Mount Horizontal Tenon and<br>adjusted horizontally.  | 12"<br>\$2.6"<br>\$2.6"<br>\$2.6"<br>\$2.6"<br>\$4.4"  | Quad 90° Horizontal Tenon Adapter<br>WSD-SB2.5QD90-D<br>MAX EPA: 0.3<br>Finish: Dark Bronze<br>The Bracket is designed to mount ove<br>2-3/8" (60mm) O.D. vertical tenon. Fo<br>fixtures can be mounted to the Round<br>External Mount Horizontal Tenon and<br>adjusted horizontally.   |
| 10.23"<br>02.36"<br>02.677"<br>02.677"<br>03"  | Single Spoke Bracket Tenon Adapter<br>WSD-SB2.5S90-D<br>MAX EPA: 0.4<br>Finish: Dark Bronze<br>The Bracket is designed to mount over<br>2-3/8" (60mm) O.D. vertical tenon. One<br>fixtures can be mounted to the Round<br>External Mount Horizontal Tenon and<br>adjusted horizontally.  | 2.6 <sup>°</sup><br>4.4 <sup>°</sup><br>02.67 <sup>°</sup><br>03 <sup>°</sup><br>02.36 <sup>°</sup>  | Double 180° Horizontal Tenon Adapter<br>WSD-RB2.5D180-D<br>MAX EPA: 0.9<br>Finish: Dark Bronze<br>The Bracket is designed to mount ove<br>2-3/8" (60mm) O.D. vertical tenon. Tw<br>fixtures can be mounted to the Round<br>External Mount Horizontal Tenon and<br>adjusted horizontally.  |
| €21.5 <sup>%</sup><br>(•2.36 <sup>°</sup><br>•2.67 <sup>°</sup><br>•2.67 <sup>°</sup><br>•2.67 <sup>°</sup><br>•2.36 <sup>°</sup><br>•2.36 <sup>°</sup><br>•2.36 <sup>°</sup><br>•2.36 <sup>°</sup><br>•2.36 <sup>°</sup>  | Triple 180° Horizontal Tenon Adapter       WSD-RB2.5TR180-D       MAX EPA: 1.4       Finish: Dark Bronze       The Bracket is designed to mount over       2-3/8" (60mm) O.D. vertical tenon. Three       fixtures can be mounted to the Round       External Mount Horizontal Tenon and       adjusted horizontally.  | 2.67°  | Quad 90° Horizontal Tenon Adapter<br>WSD-RB2.5QD90-D<br>MAX EPA: 1.5<br>Finish: Dark Bronze<br>The Bracket is designed to mount ove<br>2-3/8" (60mm) O.D. vertical tenon. For<br>fixtures can be mounted to the Round<br>External Mount Horizontal Tenon and<br>adjusted horizontally.  |
| 10.236<br>10.39<br>20.23   | 90° Wall Mount Bracket with 2-3/8" 0.D. Tenon<br>WSD-ADP2.5-90H-D<br>MAX EPA: 0.7<br>Finish: Dark Bronze<br>The 90° wall mount bracket with 2-3/8"<br>tenon attaches flood and area fixtures to<br>almost any surface: wall, roof, or wood<br>pole. Provides wiring access and abuilt-in<br>2-3/8" O.D. tenon to mount a fixture with<br>our adjustable slip-fitter. Suggested 3/8"<br>diameter bolts for mounting. Mounting<br>holes are spaced 3-1/4" apart. | 3"2.75"<br>7.87"<br>10.6"  | Double 180° Horizontal Tenon Adapter<br>WSD-RB2.5TR180H-D<br>MAX EPA: 1.0<br>Finish: Dark Bronze<br>The Bracket is designed to mount ove<br>2-3/8" (60mm) O.D. vertical tenon. Tw<br>fixtures can be mounted to the Round<br>External Mount Horizontal Tenon and<br>adjusted horizontally.  |
| 62.37 tiOmi<br>15° (Hami)<br>10° ( | Triple 120° Horizontal Tenon Adapter<br>WSD-SB2.5TR120V-D<br>MAX EPA: 1.5<br>Finish: Dark Bronze<br>The Bracket is designed to mount over<br>2-3/8" (60mm) O.D. vertical tenon. Three<br>fixtures can be mounted to the Round<br>External Mount Horizontal Tenon and<br>adjusted horizontally.   | 2.86.3" (180mm)<br>2.86.3" (180mm)<br>2.72" (120mm)<br>4.92" (120mm)<br>4.92" (120mm)<br>4.92" (120mm)<br>4.92" (120mm)<br>4.92" (120mm)<br>4.92" (120mm)<br>4.93" (120mm)<br>4. | Double 180° Wall Mount Bracket with 2-3/4       0.D. Tenon       WSD-ADP2.5-180H-D       MAX EPA: 1.4       Finish: Dark Bronze       The 180° wall mount bracket with 2-3/4       tenon attaches flood and area fixtures almost any surface: wall, roof, or wood pole. Provides wiring access and abui 2-3/8" O.D. tenon to mount a fixture w our adjustable slip-fitter. Suggested 3/4       diameter bolts for mounting. Mounting holes are spaced 3-1/4" apart. |

#### www.lightbulbsurplus.com | sales@lightbulbsurplus.com

# **Light Pole Accessories**

## Size: 4" (4" × 4"), 5" (5" × 5")



| MOUNTING OPTIONS:   |   |  |   |
|---|---|--|---|
| 5.04" (128mm)<br>63" (100mm)<br>(02.91" (74mm)<br>28" Niemsi                  | WSD-NEWSBARM2-D<br>Finish: Dark Bronze<br>Arm Mount 4" and 5" Square and Round<br>poles. Standard versatile mounting arm<br>is simple to install and can be used with<br>existing poles for retro installations.  | 6.5" (165mm)<br>5" (127mm)<br>40.51" (13mm)<br>42.55" (65mm) 3.11" (79mm)  | WSD-NEWSBSF2-D<br>Finish: Dark Bronze<br>Slipfitter Mount An optional cast aluminum<br>mast arm adapter secures fixture head to<br>nominal 2"(2-3/8"O.D. pipe size) horizonta<br>steel tenon arm.   |
| 12.95° (75mm)<br>12.95° (75mm)<br>100,5mm)<br>2.527 (00,5mm)<br>47° (100,5mm) | WSD-SBT-D<br>Finish: Dark Bronze<br>Easy to install for direct wall mounting with<br>1/2" conduit wiring.   | 6.5" (165mm)<br>5" (127mm)<br>6.3" (166mm)<br>6.3" (166mm)<br>6.3" (166mm)<br>6.3" (166mm)<br>0.31" (8mm)  | WSD-SFARM2-D<br>Finish: Dark Bronze<br>SFARM2 Mount An optional cast aluminur<br>mast arm adapter secures fixture head to<br>nominal 2"(2-3/8"O.D. pipe size) horizonta<br>steel tenon arm.   |
| and the second  | Anchor Bolt<br>WSD-BMS-S<br>Finish: Silver<br>Before installing the lamp pole, the instal-<br>lation hook should be buried underground<br>and fixed by cement After fixing, the lamp<br>pole should be fixed by locking screw and<br>base installed.                | A TO DECEMBER OF THE OWNER   | Anchor Bolt Positioning Plate<br>WSD-SPP-D<br>Finish: Dark Bronze<br>This is a screw rod positioning plate. After<br>the screw rod of the lamp rod base is fixed<br>underground, the positioning plate is fixed<br>with the screw rod to prevent the screw<br>rod from deviation. Finally, the lamp rod<br>is locked. |
| P. (FSJund)   | Install Base Shield<br>WSD-IBS4-D<br>Finish: Dark Bronze<br>The 4" Installation of base shield is used<br>to protect the base after fixing the lamp<br>pole, so that the lamp pole base is not<br>damaged, thereby increasing the service<br>life of the lamp pole. | to razimmi | Install Base Shield<br>WSD-IBS5-D<br>Finish: Dark Bronze<br>The 5" Installation of base shield is used<br>to protect the base after fixing the lamp<br>pole, so that the lamp pole base is not<br>damaged, thereby increasing the service<br>life of the lamp pole.   |
| ∞2.5" 5.9"   2.6" 2",   ∞0.7" ∞0.35"  | Arm Square Tube Turn Tube Tenon Adapter<br>WSD-ARM-BAR-D<br>Finish: Dark Bronze<br>Round tube light bar installation, with Arm<br>installation of lamps.  |  | Arm Square Tube Turn Tube Tenon Adapter<br>WSD-SADP-BAR-D<br>Finish: Dark Bronze<br>Round tube light bar installation, with Arm<br>installation of lamps.   |

LIGHT POLE TOP



### www.lightbulbsurplus.com | sales@lightbulbsurplus.com